QUICK REFERENCE GUIDE > RGV3-366-L

# Gas Range, 36", 6 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Professional style with power. 17,000 BTU gas burners paired with a large capacity gas oven.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 5.3 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

# **DIMENSIONS**

Height	35 3/4 - 36 3/4'
Width	35 7/8'
Depth	29 1/8′

# **FEATURES & BENEFITS**

### **GENEROUS CAPACITY**

Featuring a generous total capacity of 5.3 cu ft, with enough room to fit a 32 lb turkey and full-sized baking sheets.

### COOKTOP POWER

Sealed Dual Flow Burners<sup>™</sup> deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

### COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

### **DESIGN QUALITY**

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

## **EASY TO CLEAN**

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

## **TOTAL CONTROL**

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

# **SPECIFICATIONS**

Accessories (sold separately)	)
Square handle option	AH-R36
Burner ratings	
Maximum burner power	17000 BTU
Power back centre	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front left	17000BTU
Power front right	17000BTU
Total cooktop power	88000 BTU
Capacity	
Shelf positions	5
Total capacity	5.3cu ft
Usable capacity	4cu ft
Controls	
Electric circuit	3 wire
Metal illuminated dials	•
Gas Requirements	
Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (LPG)	11" to 14" W.C
Oven features	
Auto re-ignition system	•
B 11	

Broil pan

QUICK REFERENCE GUIDE > RGV3-366-L Date: 06.07.2023 > 2

Over functions	
Titanium coated, illuminated	•
Titanium aastad illuminatad	
Internal light	•
Infrared Broiler	•
Full extension telescopic	•
Electronic oven control	•

Oven f	unctions		
Bake			
Broil			
Conve	ction bake		
Numbe	er of functions		
Slow c	ook		

Bake power	21,500 BTU
Broil power	19,000 BTU

Oven performance

Power requirements	
Amperage	15A
Rated current	15A
Supply frequency	60Hz

Product dimensions	
Depth	29 1/8"
Height	35 3/4 - 36 3/4"
Width	35 7/8"

Rangetop features	
Sealed range top	•
Vent trim included	•

# **Recommended Back Guards Ventilation**

Combustible situation	BGRV3-3036H
Non combustible situation	BGRV2-3036 / BGRV2-1236
Recommended hood	HCB36-6_N (36" Professional

Safety	
ADA compliant	•
Full extension telescopic	•
SKU	82003

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

# Other product downloads available at fisherpaykel.com



User Guide



Guide d'utilisation FR



Service & Warranty



Guide d'installation FR



Installation Guide

