

# Gas Range, 30", 4 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes
- Made from quality materials and real stainless steel

## DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	29 7/8"
Depth	29 1/8"

## FEATURES & BENEFITS

### COOKTOP POWER

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

### COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

### DESIGN QUALITY

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

### EASY TO CLEAN

With a continuous, porcelain basepan, cleaning up spills is effortless. Your cooktop simply needs a quick wipe to keep it looking good as new.

### TOTAL CONTROL

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

## SPECIFICATIONS

### Accessories (sold separately)

Square handle option	AH-R30
----------------------	--------

<b>Burner ratings</b>	
Maximum burner power	17000 BTU
Power back left	13000BTU
Power back right	13000BTU
Power front left	17000BTU
Power front right	15000BTU
Total cooktop power	58000 BTU

### Capacity

Shelf positions	5
Total capacity	4.6cu ft
Usable capacity	3.4cu ft

### Cleaning

Easy clean porcelain basepan	•
------------------------------	---

### Controls

Electric circuit	3 wire
Metal illuminated dials	•

### Gas Requirements

Fitting and pipe	½ NPT, min. ⅝" flex line
Supply Pressure (LPG)	11" to 14" W.C

### Oven features

Auto re-ignition system	•
Broil pan	•
Electronic oven control	•
Full extension telescopic	•

Infrared Broiler	•
Internal light	•
Titanium coated, illuminated	•

Oven functions

Bake	•
Broil	•
Convection bake	•
Number of functions	4
Slow cook	•

Oven performance

Bake power	21,500 BTU
Broil power	19,000 BTU

Power requirements

Amperage	15A
Rated current	15A
Supply frequency	60Hz

Product dimensions

Depth	29 1/8"
Height	35 3/4 - 36 3/4"
Width	29 7/8"

Rangetop features

Sealed range top	•
Vent trim included	•

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3030H
Non combustible situation	BGRV2-3030 / BGRV2-1230
Recommended hood	HCB30-6_N (Professional

Safety

ADA compliant	•
Full extension telescopic	•

SKU	82005
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- ↓ User Guide
- ↓ Guide d'utilisation FR
- ↓ Service & Warranty
- ↓ Guide d'installation FR
- ↓ Installation Guide



A PEACE OF MIND SALE  
24 Hours 7 Days a Week Customer Support  
T 1.888.936.7872 Wwww.fisherpaykel.com