QUICK REFERENCE GUIDE > CPV3-485GD-L Date: 06.07.2023 > 1

Gas Rangetop, 48", Griddle, I PG

Series 9 | Professional

Stainless Steel | LPG



A powerful five burner rangetop with Professional styling and the additional cooking flexibility of a stainless steel griddle.

- Your burners can deliver anything from very high 19,000 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- The stainless steel griddle is great for cooking anything from pancakes to bacon, grilled cheese to quesadillas
- Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16′
Width	47 7/8′
Depth	28'

FEATURES & BENEFITS

COOKTOP POWER

Sealed Dual Flow Burners™ deliver rangetop power up to 19,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

PRECISE CONTROL

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

COOKING FLEXIBILITY

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

EASY TO CLEAN

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

INFORMATION AT A GLANCE

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

DESIGN QUALITY

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron grates, and titanium coated dials.

SPECIFICATIONS		
Burner ratings		
Max burner power	Yes	
Power back left	11,500 BTU	
Power back right	11,500 BTU	
Power front centre	19,000 BTU	
Power front left	15,000 BTU	
Power front right	15,000 BTU	
Power griddle	24,000 BTU	
Total cooktop power	96,000 BTU	
Cleaning		
Easy clean porcelain basepan	•	
Controls		
Metal illuminated dials	•	
Star K Certification	•	
Titanium coated, illuminated	•	
Gas Requirements		
Fitting and pipe	½ NPT, min. 5%" 🛭 flex line	
Supply Pressure (LPG)	11" to 14" W.C	

Performance

Sealed Dual Flow Burners™	5
Sealed cooking surface	•
Sealed range top	•
Simmer on all burners	140°F

QUICK REFERENCE GUIDE > CPV3-485GD-L

Date: 06.07.2023 > 2

Power requirements	
Amperage	15A
Supply frequency	60Hz
Supply voltage	120V
Product dimensions	
Depth	28"
Height	8 5/16"
Width	47 7/8"
Recommended Back Guards V	entilation
Combustible situation	BGCV2-3048H
Non combustible situation	BGCV2-3048 / BGCV2-1248
Pro hood	HCB48-12_N
Safety	
ADA compliant	•
Warranty	
Parts and labour	2 years
Zone ratings	
Front right	18500 BTU

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and

specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Guide d'utilisation FR



Service & Warranty



Installation Guide



Guide d'installation FR



Data Sheet Gas Rangetop and High Shelf High Backguard



Data Sheet Gas Rangetop and Low Backguard



Data Sheet Gas Rangetop



Data Sheet Gas Rangetop and Low Shelf High Backguard

24/7

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com