QUICK REFERENCE GUIDE > CPV3-366-L Date: 06.07.2023 > 1

Gas Rangetop, 36", LPG

Series 9 | Professional

Stainless Steel | LPG



Cook with the power and precision of a professional, with this large cooking space that includes six gas burners.

- Your burners can deliver anything from very high 19,000 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- Designed to match Professional style appliances
- Made from quality materials and real stainless steel

DIMENSIONS

Height	8 5/16"
Width	35 7/8"
Depth	28"

FEATURES & BENEFITS

COOKTOP POWER

Sealed Dual Flow Burners™ deliver rangetop power up to 19,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

PRECISE CONTROL

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

COOKING FLEXIBILITY

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

EASY TO CLEAN

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

INFORMATION AT A GLANCE

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

DESIGN QUALITY

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron grates, and titanium coated dials.

SPECIFICATIONS

Burner ratings	
Max burner power	Yes
Power back centre	13,000 BTU
Power back left	13,000 BTU
Power back right	13,000 BTU
Power front centre	15,000 BTU
Power front left	19,000 BTU
Power front right	19,000 BTU
Total cooktop power	92,000 BTU
Cleaning	
Easy clean porcelain basepan	•
Controls	
Metal illuminated dials	•
Star K Certification	•
Titanium coated, illuminated	•
Gas Requirements	
Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (LPG)	11" to 14" W.C
Performance	
Sealed Dual Flow Burners™	6
Sealed cooking surface	•
Simmer on all burners	140°F
Power requirements	
Amperage	15A
Supply frequency	60Hz

QUICK REFERENCE GUIDE > CPV3-366-L Date: 06.07.2023 > 2

Supply voltage	120V		
Product dimensions		Oth	er product downloads available at fisherpaykel.com
Depth	28"	<u></u>	User Guide
Height	8 5/16"	<u> </u>	Guide d'utilisation FR
Width	35 7/8"	<u>↓</u>	Service & Warranty
Recommended Back Guards	Ventilation	<u></u>	Installation Guide
Combustible situation	BGCV2-3036H	<u> </u>	Guide d'installation FR
Non combustible situation	BGCV2-3036 / BGCV2-1236	<u> </u>	Data Sheet Gas Rangetop and Low Thin Backguard
Pro hood	HCB36-12 N / HCB36-6 N	<u></u>	Data Sheet Gas Rangetop and High Thick Backguard with Angled Trim
Safety		<u> </u>	Data Sheet Gas Rangetop
ADA compliant	•	<u></u>	Data Sheet Gas Rangetop and High Thin Backguard
Warranty			
Parts and labour	2 years		

82017

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

SKU

