Warming Drawer, 30"

Series 9 | Professional

Stainless Steel



Keep plates warm until ready to serve; rapid proof or slow cook. Pair with a Professional-style oven for design cohesion.

- A companion product, designed to match with other Professional style Fisher & Paykel products
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	10 11/16″
Width	29 15/16″
Depth	22 3/8"

FEATURES & BENEFITS

COMPLEMENTARY DESIGN

Our Warming Drawer comes in brushed stainless steel, for seamless pairing with our matching ovens.

MULTI-FUNCTION FLEXIBILITY

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

EASY TO CLEAN

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

EASY TO USE

Soft-close with capacitive touch controls, our Warming Drawer comes with an accessory rack for optimising space.

PRECISE CONTROL

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

SAFE AND SOUND

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Accessories

Wire shelf

Capacity 42lb Accessory rack maximum Cappuccino cups 24 Espresso cups 54 Maximum allowable weight 55lbs Place settings 16 Usable depth 16 1/16" Usable height 9 1/16" Usable width 21 1/2"

Cleaning

Easy clean smooth-glass base

Controls

Audio feedback	•
Automatic timers	30', 45', 1h, 2h, 4h, 6h
Electronic capacitive touch	•
On/Off indicator	•
Pre-set heating functions	•
Sabbath mode	•
Soft close drawer	•
Standby mode	•

Functions

1

Cups	•
Dehydrate	•
Number of functions	6
Plates	•
Slow cook	•

QUICK REFERENCE GUIDE > WB30SPEX1

Warm

Performance	
Heated glass base and fan	•
Low temperature cooking	•
Temperature levels	6
Temperature range	95°F-185°F

Power requirements

Amperage	10A
Power outlet	3-prong grounding-type
Supply frequency	60Hz
Supply voltage	110V

Product dimensions

Adjustable front door panel to	•
Depth	22 3/8″
Height	10 11/16″
Width	29 15/16″

Safety

Automatic turn off after 12

Full extension slides

Warranty

Parts and labour	

82115

2 years

.

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

<u> </u>	User Guide
<u>+</u>	Guide d'utilisation FR
<u>+</u>	Service & Warranty
<u> </u>	Installation Guide
<u>↓</u>	Guide d'installation FR
<u>+</u>	Data Sheet Warming Drawer
<u>+</u>	Planning Guide - Professional Triple Stack Install



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com