DENON°



DENON DCD-1700NE

DCD-1700NE CD/SACD player with Advanced AL32 Processing Plus

Enjoy pristine high-resolution audio from CD and SACD playback on the Denon DCD-1700NE with Advanced AL32 Processing Plus and ultra-precision D/A converter.

HIGHLIGHTS	YOUR BENEFITS
Advanced AL32 Processing Plus	Experience audio beautifully faithful to the original sound. Advanced AL32 Processing Plus algorithms restore information that was lost during the digital recording.
Extended disc format support	Enjoy extended disc support for your high-resolution audio collection, including CDs, Super Audio CDs, as well as DSD and high-res files up to 192 kHz/24 bits recorded on DVD-R/RW and DVD+R/RW discs.
Proprietary disc drive	The Denon original disc drive is built with a high-class S.V.H. (Suppress Vibration Hybrid) mechanism. All elements of the design are focused on delivering optimal accuracy.
Sound Master tuned	Carefully tuned with selected audio components and evaluated by the Denon Sound Master to meet Denon's high standards and distinctive sound for an amazing experience.
DAC Master Clock design	The precisely crafted master clock design includes a high-quality oscillator to suppress jitter, ensure peak precision in D/A conversion, and optimize digital audio circuitry.
Vibration-resistant design	Designed to minimize the vibration of the chassis and reduce the adverse audio effects of heavy components so that sound quality meets Denon standards.
Over a century of audio firsts	Founded in 1910, Denon has a deep heritage of "firsts" in audio technology. This focused R&D investment ensures you get the latest technology and highest quality with every listening experience.



Advanced AL32 Processing Plus

The latest in analog waveform reproduction technology, Advanced AL32 Processing Plus uses data interpolation algorithms, up-sampling, and bit-extension to support high-resolution audio. The resulting playback is highly detailed, free of interference, richly expressive in the lower range, and beautifully faithful to the original sound.

Denon original disc drive design

The disc drive is built with a high-class S.V.H. (Suppress Vibration Hybrid) mechanism. New, condensed signal paths and circuitry that control pickup and decode noise are minimized to prevent excess noise and preserve sound quality. The hybrid construction of the S.V.H. loader provides stability in the disc drive, allowing for the decoding and signal reading with the upmost accuracy. The low center of gravity of the mechanism suppresses vibration both inside and outside the structure. By eliminating excess vibration, servo-related operations are minimized. The reduction of unnecessary controls and current consumption allows for digital signals to be read from the disc with optimal accuracy.

Hi-Res Audio support

The ability to decode Hi-Res Audio ALAC, FLAC, and WAV lossless files up to 24-bit/192-kHz, as well as DSD 2. 8 MHz and 5. 6MHz tracks (the audiophile format of SACD) lets you enjoy each note exactly as the artist intended.

DAC Master Clock design

To accurately synchronize digital circuits, the DAC Master Clock design treats the DAC as the master when clock signals are supplied. Crafted with exceptional quality, the master clock is right next to the DAC, which suppresses jitter and ensures peak precision in D/A conversion. It serves as the reference for semiconductor operation and optimizes digital audio circuitry. Two integrated clock oscillators reduce phase noise, each addressing a sampling frequency (44.1 kHz and 48kHz).

Pure Direct mode

Pure Direct mode ensures clean, detailed, and accurate audio output.

Advanced circuitry with minimized signal path

Circuit patterns are thoughtfully engineered to make signal paths as short as possible. With shorter circuits, the interference between circuits and left and right channels is reduced, and the adverse influences on audio signals are minimized. As a result, the circuit paths in the DCD-1700NE reproduces sound that's clean, highly transparent, and faithful to the original recording

Specifications				Controls		
SACD: 2Hz-		0kHz (-3dB) Hz (-0.5dB)	Remote Controller	System Remote (Amp and CD Player Control)		
Harmonic Distortion SACD: 0.00 CD: 0.0016			On-Product Buttons	Power, Disc Layer, Pure Direct, Play/Pause		
Signal-to-Noise Ratio SACD: 119d CD: 117dB			LED	Stop, Fwd/Rev, Open/Close Power: 1 (Green)		
Dynamic Range		SACD: 112dB CD: 101dB		Front Panel Display	Single Line	
				Dimmer for Front Display	Bright / Dim / Dark / Of	
Line Output Level 2.0Vrms		2.0Vrms (10	konm)	Control with App via Network Player	Yes	
Digital Audio				(Use Remote Control Bus)		
DAC Circuit TI Advanced Curren PCM1795(192k/32bit'			Others			
P		· ·	k/32b1t) ×1	Pure Direct Mode	Yes	
Digital Filter Fixed				Last Function Memory	Yes	
Digital Processing Advanced		Advanced AL	32 Processing Plus	Remote Control Bus Terminal	Yes	
DAC Master Clock Design (Not Support Network Playback)		Yes		Remote Control	Yes (controllable, PMA-1700NE)	
Disc			Battery	Yes (AAA × 2)		
Mechanism TD-505 FO		TD-505 FOR	DM	Power Cord	Yes	
		SACD/CD/CD- DVD-R/+R/-R		Other	Stereo RCA Cable × 1	
			Layer/Multi-D/M)	Timer Play (Need external audio timer)	Yes	
		Yes	Layer/Hartr D/H)	Auto Standby Mode	Auto Standby Mode	
MP3 / WMA / AAC Yes / Yes /		Ves	General			
Playability of files recorded on CD-R/RW	WAV	Yes (~48kHz/24bit)		Front Panel (Center)	Aluminum	
		Yes (~48kHz/24bit)		· ,	Aluminum	
		· · · ·		Power, Function, Open/Close buttons		
	ALAC	Yes (~48kHz/24bit)		Power Consumption	24W	
	AIFF	Yes (~48kHz/24bit)		Standby Consumption	0.1W	
Playability of files recorded on DVD R/RW	MP3 / WMA / AAC	Yes / Yes / Yes		Unit Dimensions (W × D × H)	434 × 135 × 384mm	
	WAV	Yes (~192kHz/24bit)		Cabinet Size (W \times D \times H)	434 × 135 × 374mm	
	FLAC	Yes (~192kHz/24bit)		Packaging Dimensions (W × D × H)	543 × 250 × 515mm	
	ALAC	Yes (~96kHz/24bit)		Net weight	9.0kg	
	AIFF	Yes (~196kHz/24bit)		Packaging gross weight	11.7kg	
	DSD (DIFF / DSF)	Yes (~5.6MH	z)			
Firmware Update Yes (FE/BE, MCU)		MCU)				
Inputs/Outputs	3					
Fixed Analog Output (RCA)		Cinch x 1 (Gold-Plated)				
Optical input/o	utput (Maximum Support)	0 / 1			
Coaxial input/output (Maximum Support)		0 / 1				