



Features

- 1" Beryllium Dome Tweeter
- 5th-generation Acoustic Lens Waveguide
- Deep Ceramic Composite (DCC) Cone Woofer
- High-order Crossovers with Film Capacitors and Air Core Inductors
- Magnetically Attached Grilles
- Four Premium High-gloss Finishes Available; Black, White, Walnut and Metallic Silver

Specifications

| | |
|---|---|
| Description | 2-way Bookshelf Loudspeaker |
| Low Frequency Driver Size and Material | 6.5" (165mm) Deep Ceramic Composite (DCC) Aluminum Cone with Cast Frame |
| High Frequency Driver Size and Material | 1" (25mm) Beryllium Dome with Acoustic Lens Waveguide |
| Recommended Amplifier Power | 50 – 150 Watts |
| Nominal Impedance | 8 Ohms |
| Loudspeaker Sensitivity (2.83 V/1m) | 86dB |
| Frequency Response | 46Hz – 40kHz (-6dB) |
| Crossover Frequency | 1.7kHz |
| Dimensions (H x W x D) | 15.2 x 8.3 x 10.3" (1181 x 302 x 335mm) |
| Weight | 22 lbs (9.97kg) |
| Inputs | Gold-plated Binding Posts with Shorting Straps |

