



27" SINGLE WALL OVEN

JJW2427D – 27" x 29<sup>7</sup>/<sub>8</sub>" x 25<sup>5</sup>/<sub>16</sub>"

PRODUCT DIMENSIONS



FRONT VIEW



TOP VIEW

MODEL #		JJW2427D	
		in	cm
A	Overall width		
	Euro-Style Stainless	27	68.6
	Floating Glass	26 <sup>15</sup> / <sub>16</sub>	68.4
B	Height of control panel	5 <sup>1</sup> / <sub>2</sub>	14.0
C	Space between control panel and door	<sup>7</sup> / <sub>16</sub>	1.1
D	Height to top of handle	21 <sup>7</sup> / <sub>16</sub>	54.4
E	Height of door	22 <sup>1</sup> / <sub>8</sub>	56.2
F	Height of trim	1 <sup>11</sup> / <sub>16</sub>	4.3
G	Overall height	29 <sup>7</sup> / <sub>8</sub>	75.8
H	Width of recessed oven	25 <sup>5</sup> / <sub>16</sub>	64.6
I	Width of conduit channel	2 <sup>1</sup> / <sub>2</sub>	6.4
J	Depth of recessed oven	23 <sup>3</sup> / <sub>8</sub>	58.7
K	Depth with door	24 <sup>5</sup> / <sub>16</sub>	61.8
L	Depth with handle	25 <sup>5</sup> / <sub>16</sub>	64.3
M	Depth with door fully open	45 <sup>3</sup> / <sub>8</sub>	115.3


**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.



27" SINGLE WALL OVEN

JJW2427D – 27" x 29<sup>7</sup>/<sub>8</sub>" x 25<sup>5</sup>/<sub>16</sub>"

DIMENSIONS AS INSTALLED




MODEL #		JJW2427D	
		in	cm
A	Height to top of handle	22 <sup>3</sup> / <sub>4</sub>	57.8
B	Height of trim extending below cutout	1 <sup>11</sup> / <sub>16</sub>	4.3
C	Height from top of recessed oven to top of control panel	2 <sup>15</sup> / <sub>16</sub>	7.4
D	Height from bottom of recessed oven foot to bottom of oven vent	<sup>3</sup> / <sub>16</sub>	0.5
E	Height of recessed oven	26 <sup>3</sup> / <sub>4</sub>	67.9
F	Height to top of control panel	29 <sup>7</sup> / <sub>8</sub>	75.8
G	Depth with door fully open	45 <sup>3</sup> / <sub>8</sub>	115.3
H	Depth with handle	25 <sup>5</sup> / <sub>16</sub>	64.3
I	Depth with door	24 <sup>5</sup> / <sub>16</sub>	61.8
J	Depth of recessed oven	23 <sup>1</sup> / <sub>8</sub>	58.7

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.

27" SINGLE WALL OVEN

JJW2427D – 27" x 29<sup>7</sup>/<sub>8</sub>" x 25<sup>5</sup>/<sub>16</sub>"

OPENING/CLEARANCE DIMENSIONS



FRONT VIEW

SIDE VIEW

MODEL #		JJW2427D	
		in	cm
A	Width of cabinet (min.)	27	68.6
B	Width of cutout	25 <sup>1</sup> / <sub>2</sub>	64.8
C*	Height of cutout (recommended)	28	71.2
D	Top of cutout to bottom of upper cabinet door (min.)	2 <sup>3</sup> / <sub>16</sub>	5.5
E	Bottom of cutout to top of lower cabinet door (min.)	1 <sup>1</sup> / <sub>2</sub>	3.8
F	Bottom of cutout to floor	32	81.3
G	Depth of cutout (min.)	24	61.0
H	Top of countertop to bottom of cutout (min.)	31 <sup>3</sup> / <sub>8</sub>	79.7
I	Top of cutout to underside of countertop (min.)	2 <sup>5</sup> / <sub>8</sub>	6.7
J	Bottom of cutout to floor (min.)	3 <sup>7</sup> / <sub>8</sub>	9.8
e	Recommended junction box location		


\*Will fit cutout height from 26<sup>15</sup>/<sub>16</sub>" (68.4 cm) to 29<sup>7</sup>/<sub>16</sub>" (74.8 cm).

**ELECTRICAL REQUIREMENTS**


240 volt, 20-amp fused, grounded circuit is required. A dedicated circuit is required.

The length of conduit provided is for serviceability. Do not cut the conduit. The junction box should be located 3" (7.6 cm) maximum below the support surface. Drill a 1" (2.5 cm) minimum diameter hole in the right rear or left rear corner of the support surface for access to the junction box.

**NOTE:** For under counter installation, the junction box should be located in the adjacent right or left cabinet. Drill a 1" (2.5 cm) minimum diameter hole in an upper corner of the side wall for access to the junction box.



UNDER COUNTER INSTALLATION  
(without cooktop installed above)




BACK VIEW

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.

27" SINGLE WALL OVEN – FLUSH INSTALLATION

JJW2427D – 27" x 29<sup>7</sup>/<sub>8</sub>" x 24<sup>5</sup>/<sub>16</sub>" (depth without handle)

OPENING/CLEARANCE DIMENSIONS



FRONT VIEW

SIDE VIEW

MODEL #		JJW2427D	
		in	cm
<b>A</b>	Width of flush inset cutout (min.)	27 <sup>1</sup> / <sub>4</sub>	69.2
<b>B</b>	Width of opening (min.)	25 <sup>7</sup> / <sub>8</sub>	65.7
<b>C</b>	Height of flush inset cutout (min.)	30 <sup>7</sup> / <sub>16</sub>	77.3
<b>D</b>	Height of opening (min.)	29 <sup>1</sup> / <sub>16</sub>	75.4
<b>E</b>	Bottom of cutout to floor	4 <sup>5</sup> / <sub>8</sub> - 32	11.7- 81.3
<b>F</b>	Depth of cutout (min.)	25	63.5
<b>G</b>	Bottom of cutout to floor for under counter installation	4 <sup>1</sup> / <sub>16</sub>	10.3
<b>e</b>	Recommended junction box location		

**ELECTRICAL REQUIREMENTS**

240 volt, 20-amp fused, grounded circuit is required. A dedicated circuit is required.

The length of conduit provided is for serviceability. Do not cut the conduit. The junction box should be located 3" (7.6 cm) maximum below the support surface. Drill a 1" (3.4 cm) minimum diameter hole in the right rear or left rear corner of the support surface for access to the junction box.

**NOTE:** For under counter installation, the junction box should be located in the adjacent right or left cabinet. Drill a 1" (2.5 cm) minimum diameter hole in an upper corner of the side wall for access to the junction box.

**FLUSH INSTALLATION REQUIREMENTS**


A 25" (63.5 cm) minimum cutout depth is required.

These dimensions will result in a 1/4" (0.6 cm) reveal on the top, a 1/4" (0.6 cm) reveal on the sides and a 1/8" (0.3 cm) reveal on the bottom of the wall oven.


The front face of the cleats and spacers will be visible and should be treated as a finished surface.

**CABINET REQUIREMENTS**


**NOTE:** When using under counter installation, check cabinet manufacturer's specifications to verify fit.



UNDER COUNTER INSTALLATION  
(without cooktop installed above)



TOP VIEW



BACK VIEW

\*Cleats and spacers must be recessed 1<sup>3</sup>/<sub>8</sub>" (3.5 cm) from the front of the cabinet.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.