Bowers & Wilkins

Custom Installation CWM Cinema 7







See nothing, hear everything

This speaker is designed for wall-mounted left, center and right speaker positions in a discreet home cinema system, and can be mounted beside, above or below the screen, ensuring crystal-clear dialogue and dramatic special effects.

Thanks to Bowers & Wilkins unique QuickDogs™ fixing method, installation is simple, requiring no tools. And in common with other recent CI products, it features an ultra-narrow bezel and magnetically attached metal grille, both of which can be customised to complement décor.

Technical Specifications

Description 2½-way in-wall system

Drive Units 1x Ø25mm (1 in) Nautilus™

tubeloaded aluminium dome tweeter

2x Ø100mm (4 in) blue Kevlar®

cone bass/midrange

2x Ø100mm (4 in) paper cone bass

Frequency range (-6dB) 34Hz – 50kHz

Frequency response (+/-3dB) 44Hz - 22kHz

Recommended

Amplifier Power 25W – 150W

Sensitivity 85dB (2.83V, 1m)

Nominal Impedance $8\Omega (4.5\Omega \text{ minimum})$

Frame 175mm (6.9 in) x 625mm (24.6 in)

Cut-out 147mm (5¾ in) x 597mm (23½ in)

Depth behind surface 92mm (3.6 in)

Protrusion 8.2mm (0.32 in)

Pre-mount Kit PMK CWMC7

Back Box BB LCR7

Bowers & Wilkins

www.bowers-wilkins.com

Nautilus and QuickDogs are trademarks of B&W Group Ltd. Keylar is a trademark of DuPont

Kevlar is a trademark of DuPont

Copyright © B&W Group Ltd. E&OE

