



Powered by the exclusive iQ Blower System with GPS Technology (see page 62) for the quietest, most energy efficient and fastest smoke and odor removal available in a range hood.

Perimeter aspiration provides superior ventilation, backed up by mesh grease filters.

Four-speed electronic light-touch controls are operated with the ACR3 remote control, included.

Six 3-watt LED lights provide bright cooktop lighting.

Available with Stainless Steel panels or optional White Glass Panels for a designer look.


10-minute delay-off and filter clean reminder provide convenient operation.

Designed to work with optional Automatic make-up air dampers.

Model Numbers:

CC34IQSB

CC34E6SB



Bright, energy efficient LED lighting.



Perimeter aspiration for superior capture.



Included ACR3 remote control lets the busy cook stay in control from anywhere in the kitchen.



Optional white glass panels.

Hood Sizes

Width	43-3/8"
Depth	27-1/2"

Finish

Stocked	Brushed Professional Grade Stainless Steel
Special Order	Not Available

Features

Lighting Type	LED
Number of Lamps	6 lamps (3 watts each)
Lighting Levels	1
Lighting Lamps Included	Yes
Control Type	4-speed Electronic Light Touch
Control Features	Delay-off, Filter Clean Reminder
Remote Control	ACR3 Included
Filter Type	Mesh Grease Filter with Perimeter Aspiration
Non-ducted Capability	No

Hood Blower Included (CC34IQ)

Internal	iQ6
Blower CFM	600
Sones Low/High	0.3/8.0

Hood Blower Options (CC34E blowers sold separately)

*External In-line:	ILB3	ILB6	ILB9	ILB11
Max CFM	280	600	800	1100
*External Exterior:	EB6	EB9	EB12	EB15
Max CFM	600	900	1200	1500

*Some levels using External blowers are typically half of comparable CFM Internal blowers.

Accessories


White Glass Panels	AGPCC34W
Automatic MUA Damper	MD6T, MD8T, MD10T (Requires Fresh Air Inlet)
Fresh Air Inlet	641FA, 643FA, 610FA

Installation Requirements

Electrical Amps @ 120V	Internal: 4.0, External: 6.5
Electrical connection	Direct
Duct Size—Internal Blower	8"
Duct size—External Blower	8"
Duct Direction	Horizontal Vertical (External vent only)
Backdraft Damper	Included




CC34IQSB



8" Round Duct

CC34E6SB



8" Round Duct

Installation height above the cooking surface 48" minimum, 72" maximum recommended.

