

# RGV2-485GD-N\_N Gas Range 48", 5 Burners with Griddle

#### Professional

This 48" Fisher & Paykel freestanding range gives you cooking flexibility with five high powered burners, a griddle plate and two oven cavities.

#### Stainless Steel

## Dimensions

| Depth  | 29 1/8″          |
|--------|------------------|
| Height | 35 3/4 - 36 3/4" |
| Width  | 47 7/8"          |

## **Features & Benefits**

#### Cooktop power

Sealed Dual Flow Burners<sup>™</sup> deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

#### **Total control**

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

#### Easy to clean

A sealed cooktop surface coupled with a commercial-style stainless steel finish means your cooktop simply needs a quick wipe to keep it looking good as new.

#### Instant visibility

Control dials have halo-illumination glowing white – heating up; orange – temperature reached; red – self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

#### **Cooking flexibility**

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

#### Handle option

Customise your Professional Fisher & Paykel kitchen appliance to suit your kitchen style by purchasing our square handle option.

## Specifications

#### Accessories

| Combustible situation (Sold seperately) | BGRV2-3048H             |
|---|-------------------------|
| Minimum CFM                             | 1,200                   |
| Non combustible situation (Sold         | BGRV2-3048 / BGRV2-1248 |
| seperately)                             | BGRV2-3046 / BGRV2-1246 |
| Recommended hood (Sold seperately)      | VS48-48" Pro Hood       |
| Square handle option (Sold seperately)  | AH-R48                  |
| Cleaning                                |                         |
| Dishwasher proof trivets                | •                       |
| Controls                                |                         |
| Main oven- Electronic Oven Control      | •                       |
| Main oven- Internal light               | •                       |
| Metal illuminated dials                 | •                       |
| Secondary Oven- Electronic Oven Control | •                       |
| Secondary Oven- Internal light          | •                       |
| Cooktop features                        |                         |

Gas Cooktop- Sealed range top

Vent trim included

24/7

### A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1.888.936.7872 W fisherpaykel.com

Flat vent trim

| Cooktop performance                 |                                |
|-------------------------------------|--------------------------------|
| Max burner power                    | 23500 BTU                      |
| Power back left                     | 18500 BTU                      |
| Power back right                    | 18500 BTU                      |
| Power centre                        | 23500 BTU                      |
| Power front left                    | 18500 BTU                      |
| Power front right                   | 18500 BTU                      |
| Power griddle                       | 24000 BTU                      |
| Sealed Dual Flow Burners™           | 5                              |
| Simmer on all burners               | 140 °F                         |
| Total cooktop power                 | 121500 BTU                     |
| Gas requirements                    |                                |
| Fitting and pipe                    | 1/2 NPT, min. 5/8" # flex line |
| Supply Pressure                     | NG Pressure 6" to 9" W.C       |
| Oven features                       |                                |
| Main oven- Broil pan                | •                              |
| Main oven- Infrared Broiler         | •                              |
| Main oven- Large broil pan          | ٥                              |
| Secondary Oven- 3/4 extention racks | 2                              |

| Oven functions                         |           |
|--|-----------|
| Main oven functions                    | 3         |
| Main oven- Bake                        | •         |
| Main oven- Broil                       | •         |
| Main oven- Clean                       | ٥         |
| Main oven- Convection Bake             | •         |
| Main oven- Convection Broil            | o         |
| Main oven- Proof                       | ٥         |
| Main oven- True Convection             | 0         |
| Secondary Oven- Bake                   | •         |
| Secondary Oven- Broil                  | ٥         |
| Secondary Oven- Clean                  | ٥         |
| Secondary Oven- Convection Bake        | ٥         |
| Secondary Oven- Convection Broil       | 0         |
| Secondary Oven- Fan Forced             | 0         |
| Secondary Oven- Proof                  | •         |
| Secondary oven functions               | 2         |
| Oven performance                       |           |
| Main oven- Bake                        | 29000 BTU |
| Main oven- Broil                       | 19000 BTU |
| Main oven- Shelf positions             | 5         |
| Main oven- Total Capacity (AHAM)       | 5.3 cu ft |
| Main oven- Usable Capacity (AHAM)      | 3.9 cu ft |
| Secondary Oven- Bake                   | 18000 BTU |
| Secondary Oven- Capacity total (AHAM)  | 2.4 cu ft |
| Secondary Oven- Capacity usable (AHAM) | 1.7 cu ft |
| Secondary Oven- Shelf positions        | 5         |
| Total oven capacity                    | 7.7 cu ft |

#### Power requirements

| 3 wire            | Electric circuit                   |
|-------------------|------------------------------------|
| 15                | Rated current                      |
| 60                | Supply frequency                   |
| 120               | Supply voltage                     |
|                   | Product dimensions                 |
| 29 1/8 "          | Depth (excluding handle and dials) |
| 35 3/4 - 36 3/4 " | Height (excluding vent trim)       |
| 47 7/8 "          | Width                              |
|                   | Safety                             |
| 3                 | Full extension telescopic racks    |
|                   | Style And Series                   |
| Professional      | Product Style                      |
| 71344             | SKU                                |

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2018

| Other product down | loads availab | le at fisherpa | /kel.com |
|--------------------|---------------|----------------|----------|
| fisherpaykel.com   |               |                |          |
|                    |               |                |          |
|                    |               |                |          |
|                    |               |                |          |
|                    |               |                |          |
|                    |               |                |          |
|                    |               |                |          |