Flat vent trim



RGV2-366-N_N

Gas Range 36", 6 Burners

Professional

This 36" Fisher & Paykel freestanding range has six high power burners and a large oven that can fit full size baking sheets.

Stainless Steel

Dimensions

 Depth
 29 1/8"

 Height
 35 3/4 - 36 3/4"

 Width
 35 7/8"

Features & Benefits

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Easy to clean

A sealed cooktop surface coupled with a commercial-style stainless steel finish means your cooktop simply needs a quick wipe to keep it looking good as new.

Instant visibility

Control dials have halo-illumination glowing white – heating up; orange – temperature reached; red – self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Handle option

Customise your Professional Fisher & Paykel kitchen appliance to suit your kitchen style by purchasing our square handle option.


Specifications

Cooktop features

Vent trim included

Gas Cooktop- Sealed range top

Accessories	
Combustible situation (Sold seperately)	BGRV2-3036H
Minimum CFM	600-1,200
Non combustible situation (Sold	BGRV2-3036 / BGRV2-1236
seperately)	
Recommended hood (Sold seperately)	VS36 / VS1236 -36" Pro
Recommended flood (30id seperatery)	Hood
Square handle option (Sold seperately)	AH-R36
Cleaning	
Cleaning Dishwasher proof trivets	
•	
Dishwasher proof trivets	•
Dishwasher proof trivets Controls	•



Cooktop performance	
Max burner power	23500 BTU
Power back centre	18500 BTU
Power back left	18500 BTU
Power back right	18500 BTU
Power front centre	18500 BTU
Power front left	23500 BTU
Power front right	23500 BTU
Sealed Dual Flow Burners™	6
Simmer on all burners	140 °F
Total cooktop power	121000 BTU
Gas requirements	
Fitting and pipe	½ NPT, min. %" # flex line
•	½ NPT, min. %" # flex line NG Pressure 6" to 9" W.C
Fitting and pipe	
Fitting and pipe Supply Pressure	
Fitting and pipe Supply Pressure Oven features	
Fitting and pipe Supply Pressure Oven features Main oven- Broil pan	
Fitting and pipe Supply Pressure Oven features Main oven- Broil pan Main oven- Infrared Broiler	
Fitting and pipe Supply Pressure Oven features Main oven- Broil pan Main oven- Infrared Broiler Oven functions	NG Pressure 6" to 9" W.C
Fitting and pipe Supply Pressure Oven features Main oven- Broil pan Main oven- Infrared Broiler Oven functions Main oven functions	NG Pressure 6" to 9" W.C

	Over montenance
	Oven performance
29000 BTU	Main oven- Bake
19000 BTU	Main oven- Broil
5	Main oven- Shelf positions
5.3 cu ft	Main oven- Total Capacity (AHAM)
4 cu ft	Main oven- Usable Capacity (AHAM)
5.3 cu ft	Total oven capacity
	Power requirements
3 wire	Electric circuit
15	Rated current
60	Supply frequency
120	Supply voltage
	Product dimensions
29 1/8 "	Depth (excluding handle and dials)
35 3/4 - 36 3/4 "	Height (excluding vent trim)
35 7/8 "	Width
	Safety
3	Full extension telescopic racks
	Style And Series
Professional	Product Style
71354	SKU

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2018

Other product downloads available at fisherpaykel.com

fisherpaykel.com