

RGV2-364GD-L_N Gas Range 36", 4 Burners with Griddle (LPG)

Professional

This 36" Fisher & Paykel freestanding range gives you cooking flexibility with four gas burners, a griddle and a large oven.

Stainless Steel

24/

Dimensions

| Depth | 29 1/8" |
|--------|------------------|
| Height | 35 3/4 - 36 3/4" |
| Width | 35 7/8" |

Features & Benefits

Cooktop power

Sealed Dual Flow BurnersTM deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the haloilluminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Easy to clean

A sealed cooktop surface coupled with a commercial-style stainless steel finish means your cooktop simply needs a quick wipe to keep it looking good as new.

Instant visibility

Control dials have halo-illumination glowing white – heating up; orange – temperature reached; red – self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Handle option

Customise your Professional Fisher & Paykel kitchen appliance to suit your kitchen style by purchasing our square handle option.

Specifications

Power griddle

Sealed Dual Flow BurnersTM

Simmer on all burners

Total cooktop power

| Accessories | |
|---|-----------------------------|
| Combustible situation (Sold seperately) | BGRV2-3036H |
| Minimum CFM | 600-1,200 |
| Non combustible situation (Sold seperately) | BGRV2-3036 / BGRV2-1236 |
| Recommended hood (Sold seperately) | VS36 / VS1236 -36" Pro Hood |
| Square handle option (Sold seperately) | AH-R36 |
| Cleaning | |
| Dishwasher proof trivets | • |
| Controls | |
| Main oven- Electronic Oven Control | • |
| Main oven- Internal light | • |
| Metal illuminated dials | |
| Cooktop features | |
| Gas Cooktop- Sealed range top | • |
| Vent trim included | Flat vent trim |
| Cooktop performance | |
| Max burner power | 19000 BTU |
| Power back left | 13000 BTU |
| Power back right | 13000 BTU |
| Power front left | 19000 BTU |
| Power front right | 15000 BTU |
| | |



FISHER & PAYKEL

18000 BTU

78000 BTU

4

140 °F

SPEC SHEET > RGV2-364GD-L_N > Gas Range 36", 4 Burners with Griddle (LPG)

| Gas requirements | |
|------------------------------------|------------------------------|
| Fitting and pipe | 1/2 NPT, min. #" # flex line |
| Supply Pressure | LPG Pressure 11" to 14" W.C |
| Oven features | |
| Main oven- Broil pan | • |
| Main oven- Infrared Broiler | • |
| Oven functions | |
| Main oven functions | 3 |
| Main oven- Bake | • |
| Main oven- Broil | • |
| Main oven- Convection Bake | |
| Oven performance | |
| Main oven- Bake | 22000 BTU |
| Main oven- Broil | 19000 BTU |
| Main oven- Shelf positions | 5 |
| Main oven- Total Capacity (AHAM) | 5.3 cu f |
| Main oven- Usable Capacity (AHAM) | 4 cu f |
| Total oven capacity | 5.3 cu f |
| Power requirements | |
| Electric circuit | 3 wire |
| Rated current | 15 |
| Supply frequency | 60 |
| Supply voltage | 120 |
| Product dimensions | |
| Depth (excluding handle and dials) | 29 1/8 |
| Height (excluding vent trim) | 35 3/4 - 36 3/4 ' |
| Width | 35 7/8 |

Safety

| Professional |
|--------------|
| 71353 |

You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2018

Other product downloads available at fisherpaykel.com fisherpaykel.com