

# CINGOLI ISLAND



LED light with dimmer

Designed to be suspended above a kitchen island, Cingoli takes flight with graceful 36" or 42" arched glass wings, which allow natural light to illuminate the surface below. The expansive glass wings are complemented by reflective stainless steel. The beauty of Cingoli is combined with features such as a powerful 600 CFM blower, dishwasher-safe stainless steel microhole filter and glass touch controls that deliver convenience and safety.

Designed for standard ducted installation, Cingoli can also be installed as a recirculating system using the Recirculating Kit, available as an accessory.

## **TECHNE SERIES**

# **Dimensions | Models**

36"W x 25 3/16"D x 1 15/16"H | ECN636S3 CINGOLI 36"

42"W x 25 3/16"D x 1 15/16"H | ECN642S3 CINGOLI 42"






## CINGOLI

PLUS

### FEATURES

Size (in) & Type	36" or 42" wide Island Chimney	
Finish	Stainless Steel + Black Glass	
Controls	Touch Control 3S + Booster	
Illumination	2 Premium LED Dimmable Lights	
Installation Type	Ducted, Recirculating Kit sold seperatly	
Blower Type	Speed 1, 160 CFMs Speed 2, 280 CFMs Speed 3, 470 CFMs Speed 4, 600 CFMs	
Filter Type	Dishwasher- Safe, Staineless Steel Microhole Filter	
Noise (sones) *Working speed:	Min: 2.36, Max: 6 Sones	
Duct Transition	Round 6"/150cms	
Electrical	120 Volts, 60 Hertz, 394 Watts, 3.27 Amps	

## LINE DRAWING



	ECN636S3	ECN642S3
А	36" (91.44 cm)	42″ (106 cm)
В	25 ¼" (64 cm)	
C*	Max: 49 <sup>1</sup> ½2" (125.3 cm) Min: 29 <sup>1</sup> ½2" (74.5 cm)	
D**	Max: 44 2 <sup>/</sup> / <sub>4</sub> " (112.4 cm) Min: 29 1 <sup>/</sup> / <sub>2</sub> " (74.5 cm)	
E	6″ (15.24 cm)	
F	12" (30.5 cm)	
G	135⁄4 ″ (33.2 cm)	

\* Ductless (Recirculating) version

\*\* Ducted version



AMBIENT

LED LIGHT

#### AMBIENT LIGHT

Elica studies on hood lighting leaves no stone unturned. Here we have thought about products not only able to light the cooktop, but the entire kitchen space. And so the hood is transformed: from a kitchen appliance to a true lighting element. Considering the design of Elica hoods, it is not hard to imagine how this option is unique, and represents one extraordinary point of strength for us.

#### LED LIGHT

LED lighting is undoubtedly the smartest solution in terms of energy saving. Expected life time of over 20.000 hours, represents the most remarkable advantage of LED light bulbs

#### HUSH SYSTEM

An exclusive sound deadening technology that effectively reduces sound levels by over 35%, compared to typical range hoods.

#### DIM-LIGHT

The Dimmer allows you to adjust the brightness of the light as you wish. With Elica, lighting is customized in a discreet, personal and practical way, in order to contribute in creating the perfect kitchen atmosphere.

#### TOP PERFORMANCE

Excellent performance for models equipped with this plus. High fume capturing capacity with an average aspiration range of 600 CFM's. With a noise level between 60-65 db(A) removing the maximum speed (reference point varies based on the hood category).



#### CFM REDUCTION

CFM Reduction System (CRS), is an exclusive feature to Elica hoods, which enables the installer to reduce the maximum blower CFM, to meet local code requirements.

### Accessories

#### **Optional Recirculating Kit** CODE: KIT02665 / (36", 42")

**Optional Long Chimney Extension** CODE: KIT0100317 / (36", 42")

