

PWC422418**FEATURES**

Heavy-duty stainless steel construction
Handfinished with hemmed edges and welded seams
Blower required (internal, in-line or remote blowers available)
Recessed controls for sleeker look
Infinite speed blower control
Bright halogen lighting
Heat sentry for safety
Transition with backdraft minimizes backward flow of cold air
Install with accessory duct cover for chimney-style hood
Rigorously tested in our U.S. manufacturing facilities for decades of use
Exceptional 24/7 support from our Customer Care team in Madison

ACCESSORIES

Backsplash
Backsplash with Warming Racks
Make-Up Air Damper
38" high stainless steel backsplash with or without warming racks
Make-up air damper
Inline Blowers
Internal Blowers
Remote Blowers
Pro Chimney Hood Duct Covers

Accessories available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.


**BLOWER OPTIONS**

- 300 CFM Internal
- 450 CFM Internal
- 600 CFM Internal
- 900 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

PRODUCT SPECIFICATIONS

Model	PWC422418
Dimensions	42"W x 18"H x 24"D
Weight	86 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS

