MOLF

PW362418

FEATURES

Heavy-duty stainless steel construction

Handfinished with hemmed edges and welded seams

Bright halogen lighting

Infinite speed blower control

Heat sentry for safety

Recessed controls for sleeker look

Blower required (internal, in-line or remote blowers available)

Transition with backdraft minimizes backward flow of cold air

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

ACCESSORIES

36" Recirculating Kit

Backsplash

Backsplash with Warming Racks

Horizontal Discharge Kit

Make-Up Air Damper

Recirculating Filter

Inline Blowers

Internal Blowers

Remote Blowers

Pro Wall Hood Duct Covers

Accessories available through an authorized dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.



BLOWER OPTIONS


- 300 CFM Internal
- 450 CFM Internal
- 600 CFM Internal
- 900 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote



PRODUCT SPECIFICATIONS

Model	PW362418
Dimensions	36"W x 18"H x 24"D
Weight	78 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical or Horizontal
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS

