

Integrated Amplifiers Comparison Chart

	ACE	240i	250i	340i X	600i v2	700i
Configuration	2-channel	2-channel	2-channel	2-channel	Dual-Mono	Dual-Mono
Power Output - 8Ω	50 W/ch.	50 W/ch.	50 W/ch.	100 W/ch.	125 W/ch.	175 W/ch.
Power Output - 4Ω	85 W/ch.	85 W/ch.	100 W/ch.	200 W/ch.	250 W/ch.	350 W/ch.
Single-ended inputs (RCA)	2	2	5	4	4	5
Balanced inputs (XLR)	n/a	n/a	n/a	1	1	1
Front panel input	1/8" mini-jack	1/8" mini-jack	1/8" mini-jack	1/8" mini-jack	○	○
Headphone output	●	●	●	●	○	○
Variable level output	●	●	●	●	●	●
Fixed level output	○	○	○	●	●	●
Tape Monitor Loop	○	○	○	○	○	1
DAC / Digital input	●	●	○	Optional	○	○
Phono Stage	● - MM only	● - MM only	○	Optional	○	○
S/N Ratio @ Full Power	100dB	100dB	101dB	110dB	120dB	120dB
THD @ Full Power	< 0.02%	< 0.02%	< 0.02%	< 0.05%	< 0.04%	< 0.04%
12V Trigger Output	○	○	○	●	●	●
RS-232 Port	●	●	●	●	●	●
Infra-Red (IR) Input	●	●	●	●	●	●
Home-Theater Bypass	●	●	○	●	●	●
Remote Control	CRM-3	CRM-3	CRM-3	CRM-3	FRM-3	FRM-3
Weight (lb)	24	24	22	28	48	60
Dimensions (W" x H" x D")	16.9 x 3.5 x 14.4	16.9 x 3.5 x 14.4	16.9 x 3.5 x 14.4	16.9 x 3.5 x 14.8	18.8 x 4.0 x 18.1	18.8 x 5.5 x 18.1