

FULGOR

MILANO

600 Series 36" Induction Range

F6PIR365S1



Series

Size
Main Colour
Logo
Stainless Steel Aesthetics

600
FULL ELECTRIC
36"
SS
•
Professional

Cooktop

Type

Cooking Surface
Knobs

INDUCTION

Ceramic Glass
•

Induction Special Features

Pot Detection System
Child lock function
Cooling fan system
Failure Codes indication

•
•
•
•

Induction Control Features

Knob for power setting (illuminated)
Power levels
Digital display for power level indication
Melting Function 113°F / 45°C (inside the pot 108°F / 42°C)
Warming Function 158°F / 70°C (inside the pot 149°F / 65°C)
Booster/Fast boil function for each zone
Heat up time automatic
Residual heat indication

•
1 to 9
•
•
•
•
•
•

Cooking Zones

5

Front Left

Inductor 9" (230mm)

Power L9
Booster

2300W
3700W

Rear Left

Inductor 7" (180mm)

Power L9
Booster

1850W
3000W

Middle dual circuit

Inductor 11" (280mm)

Power L9
Booster

3000W
5500W

Middle single circuit

Inductor 7" (180mm)

Power L9
Booster

1850W
2600W

Front Right

Inductor 9" (230mm)

Power L9
Booster

2300W
3700W

Rear Right

Inductor 7" (180mm)














Power L9
Booster

1850W
3000W

FULGOR

MILANO

Oven

Type	ELECTRIC PIRO	
Oven Type	Multifunction 2 Fans (True Euro Convection)	
Temperature Regulation	Electronic (max temp. 550°F/290°C)	
Functions		
Pyrolytic Self-Clean with automatic door latch		•
True European Convection Bake (Multi level)		•
Convection Broil		•
Convection Roast		•
Pizza (Lower Convection)		•
Bake		•
Broil		•
Dehydrate		•
Thaw (Defrost)		•
Proof (Warm)		•
Keep warm (Warm Plus)		•
Oven Lights		•
Fast Preheat		•
Control Panel		
Control type	HAWK3TC - Electronic	
Clock Display	White LED	
Temperature Display	White LED	
Function Display	White LED	
Commands	6 Heavy Duty Knobs / 6 Touch Keys	
Language	English	
Electric Oven Features		
Preset/Last used temperature memory	•	
Preheat bar (25%, 50%, 75%, 100%)	•	
Automatic Fast Preheat	•	
Child Door Lock	•	
Commands Lock	•	
Sabbath mode	•	
12/24 hour clock format	•	
°C/°F	•	
Oven Door(s)		
Oven Glass Window	Deep Embossed Window	
Door Cooling System	4 Pane Heat Resistant Glass	
Soft closing system	•	
Door Hinges	Heavy Duty Steady Tilt	
Handle Style	Stainless Steel Tube d30mm, Pro Style	
Oven Cavity		
Gross Capacity (cuft)	5.7	
Usable Capacity (cuft)	4.9	
Cavity Enamel Colour	Black	
Rack Positions	6	
Oven Lights	3x20W Halogen	
Heating Element		
Broil Upper Heating Element	3500 W (240V)	
Upper Auxiliary Element Wattage	1032W (240V)	
Concealed Bake Lower Heating Element	3000 W (240V)	
Convection Element Wattage	2x1300 W (240V)	
Oven Accessories		
Chromed racks	2	
Enameled Grill set (basin + anti splash)	1	
Telescopic chromed rack	1	
Meat probe	1	
Dimensions		
Overall dim - width	35 3/4" (910mm)	

FULGOR

MILANO

Height min/max 36 3/8" (925mm) / 38 1/2" (977mm)
Overall dim - depth 29 3/4" (756mm)

Power / Ratings (208/240 V, 60 Hz)

KW/Amps rating at 120-240V, 60Hz 14.6KW - 61A
KW/Amps rating at 120-208V, 60Hz 13.3kW - 63A
Cable + Plug Nema 14-50P

INSTRUCTIONS FOR USE

Use & Care Manual EN, SP, FR
Installation Manual EN, SP, FR