Bowers & Wilkins HTM2 D3



Compact centre

The HTM2 D3 is the perfect partner for the smaller speakers in 800 Series Diamond range. Boasting Diamond dome tweeters, Continuum and Aerofoil cones, crystal clear sound is guaranteed.

Technical specifications

Technical features Diamond tweeter

Continuum cone FST™ Anti-Resonance plug Aerofoil cone bass units

 $\mathsf{Flowport}^{\mathsf{TM}}$

Solid body tweeter Optimised matrix Tweeter on top

Description 3-way vented-box system

Drive units 1x ø25mm (1 in) diamond dome high-frequency

1x ø130mm (5 in) Continuum cone FST midrange

2x ø165mm (6.5 in) Aerofoil cone bass

Frequency range 33Hz to 35kHz

Frequency response (+/-3dB from reference

axis)

45Hz to 28kHz

Sensitivity 90dB

(on axis at 2.83Vrms)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m on axis)

TBC

Nominal impedance 8Ω

Recommended amplifier

power

50W - 200W into 8Ω on unclipped programme

 $\textbf{Max. recommended} \hspace{1.5cm} \textbf{0.1} \boldsymbol{\Omega}$

cable impedance

Dimensions Height: 302mm (11.9 in)

Width: 720mm (28.4 in) **Depth:** 326mm (12.8 in)

Net weight TBC

Finishes Cabinet Grille

Real wood veneers:

Rosenut Black

Painted finish:

Gloss Black
Satin White
Grey

Bowers & Wilkins

www.bowers-wilkins.com