QUICK REFERENCE GUIDE > OR30SCI6R1 Date: 09.09.2020 > 1

## Induction Range, 30", 4 Zones, Self-cleaning

Series 9 | Classic

Red



Blending heritage styling and contemporary performance, including convection oven and an instant-response induction cooktop.

- Four induction cooking zones with immediate heat response and precise control
- Convection oven with 3.5 cu ft total capacity and nine oven functions including Roast and Aero™Pastry
- Self-cleaning function breaks down food residue for an easy clean
- Non-tip full-extension shelves for safe removal of hot dishes

#### **DIMENSIONS**

Height	35 <sup>3</sup> / <sub>4</sub> - 37 <sup>5</sup> / <sub>8</sub> ′
Width	29 <sup>7</sup> / <sub>8</sub> ′
Depth	25 <sup>1</sup> / <sub>4</sub> ′

#### **FEATURES & BENEFITS**

#### **Outstanding Performance**

Discover the flexibility to get creative in the kitchen with nine oven functions including Bake, Roast, and Aero™ Pastry with Pizza Bake.

#### **SPECIFICATIONS**

Accessories

	Accessories
	2-pc grill system (Broil pan and
	Broil pan
2 sets (part 578776)	Full extension sliding shelves
3" (part 81656)	Hob rear trim (optional)
Part 81660	Kick strip, stainless steel
1 se	Pyrolytic proof shelf runners

Capacity	
Total capacity	3.6 cu ft
Usable capacity	2.9 cu ft

#### Cleaning

Acid resistant graphite enamel

Drop down grill element	•
Flat easy clean glass surface	•
Pyrolytic proof shelf runners	•
Pyrolytic self-clean	•
Removable oven door	•
Removable shelf runners	•

Controls

Oven features

Controls
Audio feedback
Automatic cooking/minute
Automatic pre-set
Celsius/Fahrenheit
Electronic clock
High resolution display
Interior light
Laser etched graphics
Precise electronic temperature
Sabbath mode
Toughened fused glass
Turned stainless steel clock
Turned stainless steel dials with

# Automatic rapid pre-heat Electronic oven control Full extension telescopic Internal light Pyrolytic proof shelf runners Pyrolytic self-clean Soft open/close door

QUICK REFERENCE GUIDE > OR30SCI6R1 Date: 09.09.2020 > 2

Oven functions	
Aero Broil	•
Aero™ Bake	•
Aero™ Pastry with Pizza mode	•
Maxi Broil	•
Number of functions	9
Pastry Bake with Pizza mode	•
Pyrolytic self-clean	•
Rapid proof	•
Roast	•
Self-clean	•
True Aero	•

Oven pe	rformance
---------	-----------

True convection

CoolTouch door	Triple glazed door
Grill power	4050W
Main Oven Shelf Positions	7
Warming drawer power	220W

#### Power requirements

Amperage	51A (Recommended Electrical
Supply frequency	60Hz
Supply voltage	120 - 240V

#### **Product dimensions**

Depth	25 <sup>1</sup> / <sub>4</sub> "
Height	35 <sup>3</sup> / <sub>4</sub> - 37 <sup>5</sup> / <sub>8</sub> "
Installation cutout dimensions	25 1/4 "

Installation cutout dimensions	30 "
Width	29 <sup>7</sup> / <sub>8</sub> "
Rangetop features	
Auto heat reduce	•
Gentle heat	2 settings
Heat settings	9
Induction cooking technology	•
PowerBoost	•
PowerBoost all zones	up to 3000W
Rangetop Performance	
Left front zone rating	1850 - 3000W
Left rear zone rating	1850 - 3000W
PowerBoost all zones	up to 3000W
Right front zone rating	1400 - 2200W
Right rear zone rating	2300 - 3700W
Safety	
Advanced cooling system	•
Anti-tilt bracket	•
Balanced oven door	•
Catalytic venting system	•
Child lock	•

Spill containment	1/8 gallon
Spillage auto off	•
Surface hot indicators	•
Warranty	
Parts and labour	2 years
SKU	81964

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ® Fisher & Paykel Appliances Ltd 2019.

CoolTouch door

Non-tip shelves

Full extension telescopic

Pan detection system
Safety time out

QUICK REFERENCE GUIDE > OR30SCI6R1 Date: 09.09.2020 > 3

### Other product downloads available at fisherpaykel.com



User Guide



Energy Label



Service & Warranty Booklet



Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

**T** 1300 650 590 **W** www.fisherpaykel.com