# **Performance Wall Mount Series**





Today's home audio applications demand solutions which traditional designs are notable to fulfill. However, regardless of the installation, performance should never be compromised. The Performance Wall Mount Series are high performance wall mountspeakers which combine installation flexibility, simple elegant design, and renownedPSB sound.

Interior designers, architects, builders and system integrators will appreciate the elegance and highest performance levels offered by the Performance Wall Mount Series. Their slim profile allows them to hug the wall and maintain a minimal visual presence.

Beyond the visual appeal and ease of application is a sonic performance which lives up to the PSB heritage. Incorporating advanced driver and cabinet design, the PWM series offer open and constant dispersion, tonal balance and bass extension of a truly refined loudspeaker many times their size.

The PWM's can be oriented either vertically or horizontally and be used as a front left, right, centre or surround channel speakers.Whether as part of a complete on wall system, a basic TV application or as an on-wall centre channel solution for floor standing speakers; the PWM Series exceed expectations in every way.

- Slim Profile On-Wall speaker system
- All-new proprietary driver compliment
- Vertical or horizontal mounting options
- Wall mount bracket included
- LCR or for surround speaker application
- Design and final voicing engineered by Paul Barton
- Available in Satin White or Satin Black



#### www.PSBspeakers.com

## Performance Wall Mount Series






	PWM1	PWM2	PWM3
Sensitivity			
Anechoic Chamber	85dB	86dB	86dB
Typical Listening Room	87dB	89dB	89dB
Frequency response			
On Axis +/- 3db	70Hz-23kHz	70Hz-23kHz	60Hz-35kHz
LF Cutoff	50Hz	40Hz	35Hz
Impedance			
Normal	8 Ohms	8 Ohms	8 Ohms
Minimum	6 Ohms	6 Ohms	6 Ohms
Recommended Amplifier	Power (Acoustic Design)		
Tweeter (Nominal)	1" (25mm) Titanium Dome with Ferrofluid	1" (25mm) Titanium Dome with Ferrofluid	1" (25mm) Titanium Dome with Ferrofluid
Midrange (Nominal)	N/A	2 x 3" (75mm) Carbon Fibre Cone Rubber Surround Cast Basket	2 x 3" (75mm) Carbon Fibre Cone Rubber Surround Cast Basket
Woofer (Nominal)	2 x 4" (100mm) Carbon Fibre Cone Rubber Surround Cast Basket	2 x 4" (100mm) Carbon Fibre Cone Rubber Surround Cast Basket	4 x 4" (100mm) Carbon Fibre Cone Rubber Surround Cast Basket
Design Type	Bass Reflex	Bass Reflex	Bass Reflex
Construction			
Cabinet	MDF	MDF	MDF
Grille Face	Cloth	Cloth	Cloth
Frame	MDF	MDF	MDF

	PWM1	PWM2	PWM3	
mensions				
Net H	28" (711mm)	36" (914mm)	48" (1219mm)	
Net W	6.5" (165mm)	6.5" (165mm)	6.5" (165mm)	
Net D	3.38" (85mm)	3.38" (85mm)	3.38" (85mm)	
Depth With Grill	3.5" (90mm)	3.5" (90mm)	3.5" (90mm)	
Shipping Information				
Dimensions				
Shipping H	11 3/8" (288mm)	11 3/8" (288mm)	11 3/8" (288mm)	
Shipping W	32" (864mm)	42" (1067mm)	54" (1370mm)	
Shipping D	9" (228mm)	9" (228mm)	9" (228mm)	
/olume	2.02 cu ft (0.06㎡)	2.49 cu ft (0.07㎡)	3.2 cu ft (0.09㎡)	
Weight				
Vet	14 lbs (6.4 kg)	20 lbs (9.1 kg)	26.5 lbs (12 kg)	
Shipping	20.1 lbs (9.1 kg)	28 lbs (12.7 kg)	33 lbs (15 kg)	
inish				
Available Finishes	Satin	Satin Black, Satin White		
Grille Type	Magnetic, Cloth Grille			
Wall Bracket				

#### Wall Bracket

Wall Mount included for Vertical and Horizontal Mounting Note: Bracket is not designed as ceiling mount



### REAL SOUND for REAL PEOPLE www.PSBspeakers.com

All specifications are subject to change without notice. PSB Speakers reserves the right to change specifications or features without notice. © 2020 PSB Speakers, a division of Lenbrook Industries Limited. PSB is a registered trademark of Lenbrook Industries Limited. All rights reserved. No part of this publication may be reproduced, stored or transmitted in any form whatsoever without the written permission of PSB Speakers. 19-063