

CustomSound™ CS 500W Digital Subwoofer Amplifier




This digital subwoofer amplifier delivers sufficient power for up to two PSB subwoofers. The built in digital signal processor (DSP) allows the installer to create several EQ settings as well as containing profiles tailored for PSB subwoofers. A built-in limiter circuit filters the incoming information and keeps it from driving the subwoofer beyond safe operating parameters. It can be powered up by several means including signal sensing and 12 volt trigger. A rack mount kit enables the subwoofer amplifier to be mounted into a 1U rack space.

The CS 500W gives the installer the necessary power and control to seamlessly blend subwoofers into any musical or theater environment.

- 500-Watt Digital Subwoofer Amplifier
- Drives two passive subwoofers simultaneously
- DSP implementation of EQ calibrated speaker profiles
- DSP profile adjustments (movies, music, flat)
- Terminal block speaker connector accommodates ten-gauge speaker cable
- IR in with up to 4 selectable IR channels
- Auto on/off or 12V trigger in
- Low level inputs/outputs
- 1U rack height
- Removable rack ears and feet included
- Switchable power supply
- Detachable power cord
- <0.5W standby power consumption
- Gross Dimensions: 16 7/8 x 1 3/4 x 8 1/8" (W x H x D)

CustomSound™ CS 500W

Digital Subwoofer Amplifier



Frequency Range		Size (W x H x D)	
Frequency Response	20-500Hz	Net W	16 7/8"
LF Cutoff -10dB	10Hz	Net H	1 3/4"
Output Power		Net D	8 1/8"
4 ohm	500 Watts RMS	Weight	
8 ohm	250 Watts RMS	Net	8.5 lb
EQ Adjustment		Features	
EQ Adjustment	Predefined EQ curves	Selectable EQ's For different models	
Finish		1U rack spacing	
Black		Shipping Dimensions	
		Net W	21" (535mm)
		Net H	5 4/5" (147mm)
		Net D	11 1/2" (292mm)
		Shipping Weight	10.4 lb (4.7kg)

REAL SOUND for REAL PEOPLE
www.PSBspeakers.com