# T36IR905SP 36-INCH BUILT-IN FRESH FOOD COLUMN

FREEDOM® COLLECTION, PANEL-READY





### FEATURES & BENEFITS

- Full Stainless Steel Inner Liner
- Freedom® Hinge enables true flush design
- Auto Door Opening provides the opening of the door with just a slight push or pull
- ThermaFresh System, Humidity and Temperature controlled drawers
- SoftClose® Drawers for easy and controlled storage
- Sleek clean design for the perfect symmetry when paired with additional columns
- TFT control panel managing all your columns functions

TEMPERATURE RANGES	
Refrigerator	36°F (2°C) to 46°F (8°C)
Temperature Controlled Drawer	30°F (-1°C) to 38°F (3°C)
SuperCool	36°F (2°C) for approximately 6 hours
Energy Saving (Economy) Mode	43°F (6°C)

GENERAL PROPERTIES	
Home Connect™ (Wi-Fi Enabled)	Yes
Panel Ready	Yes
Reversible Door Swing	Yes
SoftClose® Door	Yes
SoftClose® Drawers	Yes
Carbon Air Filter	Yes
Lighting	LED Sidewall and Theater Lighting
Refrigerator Shelves	4
Adjustable Shelves	3
Shelf Material	Glass w/Aluminum Profile
Full Extension Drawers @ 115° Door Opening Angle	Yes
Full Extension Drawers @ 90° Door Opening Angle	Yes
General Use Drawer	1
Humidity Managed Drawer	1
Temperature Controlled Drawer	1
Door Bins	3
Gallon Door Bins	1
Door Open Alarm	Yes
Open Door Assist	Yes
Special Modes	Sabbath, Economy, Vacation
CAPACITY	
Total Capacity (cu. ft.)	20.6 cu. ft.
PERFORMANCE	
Dedicated Evaporator & Compressor System	
	Yes
Freeflow® Cold Air System	Yes
Freeflow® Cold Air System SuperCool	
*	Yes
SuperCool	Yes
SuperCool TECHNICAL DETAILS	Yes Yes
SuperCool TECHNICAL DETAILS Watts (W)	Yes Yes 350 W
SuperCool TECHNICAL DETAILS Watts (W) Current (A)	Yes Yes 350 W 15 A
SuperCool TECHNICAL DETAILS Watts (W) Current (A) Volts (V)	Yes Yes 350 W 15 A 110-120 V
SuperCool TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz)	Yes Yes 350 W 15 A 110-120 V 60 Hz
SuperCool TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.)	Yes Yes 350 W 15 A 110-120 V 60 Hz 118
SuperCool TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type	Yes Yes 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong
SuperCool TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT	Yes Yes 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong
SuperCool  TECHNICAL DETAILS  Watts (W)  Current (A)  Volts (V)  Frequency (Hz)  Power Cord Length (in.)  Plug Type  DIMENSIONS & WEIGHT  Appliance Dimensions (H x W x D) (in.)	Yes Yes 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong 83 3/4"* x 35 3/4" x 24"
SuperCool  TECHNICAL DETAILS  Watts (W)  Current (A)  Volts (V)  Frequency (Hz)  Power Cord Length (in.)  Plug Type  DIMENSIONS & WEIGHT  Appliance Dimensions (H x W x D) (in.)  Required Cutout Size (H x W x D) (in.)	Yes Yes  350 W  15 A  110-120 V  60 Hz  118  120V-3 Prong  83 3/4"* x 35 3/4" x 24"  84" x 36" x 25"
SuperCool  TECHNICAL DETAILS  Watts (W)  Current (A)  Volts (V)  Frequency (Hz)  Power Cord Length (in.)  Plug Type  DIMENSIONS & WEIGHT  Appliance Dimensions (H x W x D) (in.)  Required Cutout Size (H x W x D) (in.)  Net / Gross Weight (lbs)	Yes Yes  350 W  15 A  110-120 V  60 Hz  118  120V-3 Prong  83 3/4"* x 35 3/4" x 24"  84" x 36" x 25"
SuperCool  TECHNICAL DETAILS  Watts (W)  Current (A)  Volts (V)  Frequency (Hz)  Power Cord Length (in.)  Plug Type  DIMENSIONS & WEIGHT  Appliance Dimensions (H x W x D) (in.)  Required Cutout Size (H x W x D) (in.)  Net / Gross Weight (lbs)  EFFICIENCY	Yes Yes Yes 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong 83 3/4"* × 35 3/4" × 24" 84" × 36" × 25" 406 / 449 lbs

<sup>\*</sup>Height adjustable + / -1/2" (+ / -13 mm)

Page 1 of 3 3 / 21

# T361R905SP

### 36-INCH BUILT-IN FRESH FOOD COLUMN


FREEDOM® COLLECTION, PANEL-READY



WARRANTY	
Limited, Entire Appliance, Parts and Labor on Any Part of the Refrigerator that Fails Because of a Manufacturing Defect	2 Year
Limited Warranty for Sealed Refrigeration System*; Parts and Labor	3rd to 6th Year
Limited Warranty for Sealed Refrigeration System*; Parts Only	7th to 12th Year
Limited Warranty for Stainless Steel Rust-Through	Lifetime

<sup>\*</sup>Sealed refrigeration system includes compressor, evaporator, condenser, dryer / strainer and connection tubing

#### **CUTOUT DIMENSIONS**




Furniture return

A: Area for installation of power connection.


**B:** Area for running the water line. It is recommended that the waterbox is placed adjacent to the installation cavity, so that it can be accessed for service without uninstalling the appliance. If this is not possible, place the recessed waterbox adjacent to the water supply socket elevated at the heights as referenced in areas A and B.

**C:** Recess depth depends on kitchen design. For a flush installation, the depth needs to be at least 24 inches plus the thickness of the door panel.

Stainless steel models contain a panel-ready base unit, ready-to-install stainless steel door(s) with a right or left door swing and handle(s).




#### **TOP VIEW CLEARANCE**



\*\* Door handle must be added to this dimension

\* Depends on the thickness of the furniture door.

3/4" (19 mm) is relevant for the stainless steel door.
(special Accessory).



Page 2 of 3 3 / 21


# T361R905SP

# 36-INCH BUILT-IN FRESH FOOD COLUMN

FREEDOM® COLLECTION, PANEL-READY



#### PRODUCT AND PANEL DIMENSIONS



#### **ACCESSORIES (OPTIONAL)**

#### FLAT STAINLESS STEEL DOOR PANELS

30-Inch Flat Stainless Steel Door Panel



TFL36IR900
For use with Handle
TFL36IR905
Handleless

#### **HANDLES**

Choose between two options:

# PR36HNDL20

36-Inch Professional Series Handle

or

#### MS36HNDL20

36-Inch Masterpiece® Series Handle

#### **STORAGE**



# **SPRODBIN10**Small Produce Bin



**LPRODBIN10**Large Produce Bin



# 36PRODRAIL

36-Inch Produce Railing




#### **36HFGALBIN**

36-Inch Half Gallon Bin

# FRAMEKIT10

Freedom® Frame Kit
For any custom column installation
in 24-inch deep cutouts. With two
metal side trims whose placement
between the interior cutout wall and
the appliance helps overcome the
challenge of unfinished cabinet returns.



### **HEATRKIT20 - 13W @ 120V**

Freedom® Heater Kit When two appliances are installed side-by-side a sealing kit must be used. For combinations that involve a freezer column, this sealing kit is included. For all other (nontraditional, i.e. two wine columns, two bottom freezers, etc.) sideby-side combinations or instances where any appliances are installed less than 6-inches (152 mm) apart from one another but not connected side-by-side, purchase this kit. This kit is recommended for use with any installation in areas that are subject to humidity, or located next to an outside wall.

These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of purchase. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.

 $1\,800\,735\,4328 \mid USA\,THERMADOR.COM\mid CANADA\,THERMADOR.CA\mid @2021\,BSH\,HOME\,APPLIANCES\,CORPORATION.\,ALL\,RIGHTS\,RESERVED.\,AUGUSTA STANDARD CONTROL OF COMMON CONTROL OF COMMON CONTROL OF CONTROL OF COMMON CONTROL OF COMMON CONTROL OF C$ 

Page 3 of 3 3 / 21