


Excellence. Evolved.

This is not just another speaker range. Each new generation of 800 Series Diamond is a landmark event for Bowers & Wilkins. This is our benchmark, our icon; the most advanced range of loudspeakers we know how to make. For us, the 800 Series Diamond is everything we know, and everything we are.

805 D4

The 805 D4 standmount loudspeaker is the most compact model in the 800 Series Diamond range, but it's still packed with advanced technologies, including that all-important Diamond dome tweeter and Solid Body Tweeter-on-Top. It's proof positive that small can still be beautiful.



Solid Body Tweeter

Our iconic Solid Body Tweeter-on-Top housing features an elongated form with a longer tube-loading system, creating an even more free and open sound with high frequencies. As before, the carefully decoupled housing is milled from a single solid block of aluminium to better resist resonance.

Rear-mounted crossover

All stereo models in the new range now use rearmounted crossover designs mounted on stiff aluminium spines. This isolates the sensitive capacitors from the effects of air pressure within the enclosure.





805 D4

Technical features Diamond tweeter

Solid body Tweeter-on-Top Continuum cone bass/mid

Matrix™

Anti-Resonance plug

Flowport™

Description 2-way vented-box system

Drive units 1x Ø25mm (1in) diamond dome

high-frequency

1x ø165mm (6.5in) Continuum cone bass midrange

Frequency range 34Hz to 35kHz
Frequency response 42Hz to 28kHz

(+/-3dB from reference axis)

Sensitivity 88dB

(on axis at 2.83Vrms at 1m)

Harmonic distortion 2nd and 3rd harmonics

(90dB, 1m on axis) <1 % 90Hz – 20kHz <0.3% 120Hz – 20kHz

Nominal impedance 8Ω (minimum 4.6Ω)

Recommended amplifier power

50W - 120W into 8Ω on unclipped programme

Max. recommended cable impedance

 0.1Ω

Dimensions Height: 440mm Width: 240mm

Depth: 373mm

Net weight 15.55kg
Finishes Cabinet:

Cabinet: Grille: Gloss Black
White Grey
Satin Rosenut Black
Satin Walnut Grey