LG STUDIO

WCES6428F

1.7 / 4.7 cu. ft. STUDIO Smart wi-fi Enabled Combination Double Wall Oven

7" Color LCD Touch Display Soft Close Door Air Fry Setting InstaView® Window (WideView) Steam Sous Vide Optional Flush Installation EasyClean® LG Exclusive 4-Mode True Convection ThinQ® Technology



SUMMARY	
Туре	Combi Wall Oven
Total Oven Capacity (cu. ft.)	6.4 (Upper & Lower)
Color	Stainless Steel
UPPER OVEN FEATURES	
Capacity (cu.ft)	1.7
Interior(Cavity) - Upper MWO / Lower Oven	Stainless / Enamel Coating
Microwave Power output	950W
Microwave mode power consumption	1650W
Convection Bake mode power consumption	1600W
Broil mode power consumption	1300W
Convection Element (W)	1500W (Sheath heater)
Broil Upper Element (W)	1200W (500W Infrared Heating™ + 700W Miraclon heater)
Bake Element (W)	375W
Microwave	Yes
Convection Bake	Yes
Broil	Yes
Speed cook	Yes
- # of Defrost (4 Menu)	Meat / Poultry / Fish / Bread
- # of Defrost (4 Menu)	Meat / Poultry / Fish / Bread
- # of Sensor cook (9Menu)	Beverage / Casserole / Chicken / Pasta / Pizza / Plate of food / Rice / Soup / Vegetable
- # of Auto cook	Bacon(regular sliced) / Bagels(frozen) / Baked potatoes(7-9oz/ea) / Brownie / Cod fillets(1 lb) / Corn dog(frozen) / Fresh vegetable / Frozen chicken wings / Frozen fries / Frozen chicken nuggets / Frozen chicken wings / Frozen soft pretzels / Frozen vegetable / Garlic bread(sliced, frozen) / Hamburger(1/2" thick) / Lamb chops(1/2" thick, 6-7oz) / Meat loaf(9" X 5") / Nachos / Oatmeal / Pork chops(1/2" thick, 6-7oz) / Quinoa / Ribeye steak(1" thick 14- 15oz) / Rice / Salmon steak(1" thick) / Sausage / Sirloin steak(1" thick, 18-21oz) / Tenderloin / Vegetable- canned
- # of Soften (4Menu)	Butter / Cream Cheese / Frosting / Ice Cream
- # of Melt (5Menu)	Butter / Caramel / Cheese / Chocolate / Marshmallow
LOWER OVEN FEATURES	
Capacity (cu.ft)	4.7
EasyClean [®]	Yes

	10 mins
EasyClean(SpeedClean) time	
	Yes
Variable cleaning time	Yes
Steam Assist Steam element	
	1,960 watts
Convection Type	True Convection
Convection element	2,000 watts
Convection Fan	Single Speed
Convection conversion	Yes
Bake element	2,500 watts
Bake element type	Hidden (8 pass)
Broil element	2,500 watts inner / 1,500 watts outer
Broil element pass	8
Variable broil	Yes (Full,Center / High,Med,Low)
Oven Cooking Modes	Bake / Conv. Bake / Conv. Roast / Broil /Air Fry / Warm / Proof / Steam Cook(Steam Bake, Sous-Vide) / Auto Cook / Favorite / Clean(Self Clean, Easy Clean, Steam Main®enance)
No of Auto cook	Upper (28EA), Lower (45EA) except miscellaneous
No of Favorite	40EA
No of rack position	5
No of light	2 (Halogen Lamp)
Proof	Yes
Drying / Dehydrating	Yes
Temp probe	Yes
12 hrs. shut-off	Yes
Variable warm	Yes (High,Med,Low)
CONTROL	
Oven Control Type	Glass Touch
Display	7" TFT LCD
Language	English / Spanish / French
Clock	12 hr or 24 hr (option)
Kitchen Timer	Yes
Timed Cook	Yes
Temperature Unit of Measure	Fahrenheit / Celsius
Cooking Complete Reminder Volume	Beeper (Hi, Lo, Off)
Certified Sabbath mode	Yes
APPEARANCE	
All Available Colours	Stainless Steel
Handle	Stainless Steel
Smudge Resistant	Yes
Oven Door Feature	WideView [™] Window
InstaView®	Yes (Lower Only)

Juncy® (Wi-Fi Enabled) Yes Check & Control Yes Voice Control Yes Smart Recipe (3rd Party Recipe App) Innit, Sidechef SmartDiagnosis™ Yes DIMENSIONS/CLEARANCES/WEITS Product (Wi x H x D): Including Door 29 3/4" x 43 13/16" x 24 15/32" Product (Wi x H x D): Including Door 29 3/4" x 43 13/16" x 26 29/32" Product (Wi x H x D): Including Door 29 3/4" x 43 13/16" x 26 29/32" Product (Wi x H x D): Including Door 29 3/4" x 43 13/16" x 26 29/32" Product (Wi x H x D): Standard Xin: 28 1/2" x 43 7/16" x 24 "Max. 28 5/8" x 43 1/2" x 24" Xin: 28 1/2" x 43 7/16" x 24" Max. 20 Kat-0ut (Wi X H x D): Standard Xin: 28 1/2" x 43 7/16" x 24" Max. 20 Kat-0ut (Wi X H x D): Standard Xin: 28 1/2" x 43 7/16" x 24" Max. 20 Kat-0ut (Wi X H x D): Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Overall Depth (in) - including handle 20.8(11" (W) x 8-9/25" (H) x 17- 5/13" (D) Over Interior Dimensions (LOwer) (in) 24-1/2" (W) x 17-5/8" (H) x 18- 7/3" (D) Over Interior Dimensions (In) (W x H x D) 30" x 50" x 30" Requireed Power Supply 6	SMART FEATURES	
Check & Control Yes Voice Control Yes Smart Recipe (3rd Party Recipe App) Innit, Sidechef SmartDiagnosis™ Yes DIMENSIONS/CLEARANCES/WEUTS Product Weight (lbs) 204 Shipping Weight (lbs) 293/4" x 43 13/16" x 24 15/32" Product (W x H x D): Including Door 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Including Handle 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Including Handle 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Including handle Min. 28 1/2" x 43 7/16" x 24"Max. 28 5/8" x 43 1/2" x 24" Cut-out (W x H x D): Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Overall Depth (in) - including handle TBD Over Interior Dimensions (Uoper) (in) 24-1/2" (W) x 17-5/8" (H) x 18- 7/8" (D) Over Interior Dimensions (Lower) (in) 24-1/2" (W) x 17-5/8" (H) x 18- 7/8" (D) Over Interior Dimensions (Lower) (in) 24-1/2" (W) x 17-5/8" (H) x 18- 7/8" (D) Quere Requiree Power Supply 60 Hz / 240 V, 208 V ACCESSORIES EA Giads Tray(Upper) 1EA Rack(Upper) <td< td=""><td></td><td>Voc</td></td<>		Voc
Voice Control Yes Smart Recipe (3rd Party Recipe App) Innit, Sidechef Smart Diagnosis™ Yes DIMENSIONS/CLEARANCES/WE/FTS Product Weight (bs) 204 Shipping Weight (bs) 293/4" x 43 13/16" x 24 15/32" Product (W x H x D) : Including Door 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D) : Including Handle 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D) : Opening Door 29 3/4" x 43 13/16" x 24 15/32" Cut-out (W x H x D) : Opening Door 29 3/4" x 43 13/16" x 45 21/32" Cut-out (W x H x D) : Standard Min. 28 1/2" x 43 7/16" x 24"Max. 28 5/8" x 43 1/2" x 24" Out-out (W x H x D) : Standard TBD Overall Depth (in) - including handle TBD Overal Dimensions (Uper) (in) 20-8/11"(W) x 8-9/25"(H) x 17- 5/13"(D) Overal Interior Dimensions (Lower) (in) 24-1/2"(W) x 17-5/8"(H) x 18- 7/8"(D) Overal Interior Dimensions (I/W x H x D) 33" x 50" x 30" POWER/RATINGS 24-1/2" (W) x 17-5/8"(H) x 18- 7/8"(D) Racing 0 60 Hz / 240 V, 208 V Rating 0 60 Hz / 240 V, 208 V Rater probe 1EA Raterorop		
Smart Recipe (3rd Party Recipe App) Innit, Sidechef Smart Diagnosis™ Yes DIMENSIONS/CLEARANCES/WEIFTS Product Weight (lbs) 204 Shipping Weight (lbs) 29 3/4" x43 13/16" x 24 15/32" Product (W x H x D) : Including Door 29 3/4" x43 13/16" x 26 29/32" Product (W x H x D) : Including Indoor 29 3/4" x43 13/16" x 26 29/32" Product (W x H x D) : Opening Door 29 3/4" x43 13/16" x 26 29/32" Product (W x H x D) : Opening Door 29 3/4" x43 13/16" x 26 29/32" Cut-out (W x H x D) : Standard Min. 28 1/2" x43 7/16" x 24 "Max. 28 5/8" x43 1/2" x 24" Out-out (W x H x D) : Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Overall Depth (in) - including handle TBD Overal IDepth (in)		
SmartDiagnosis™ Yes DIMENSIONS/CLEARANCES/WE/TS Product Weight (lbs) 204 Shipping Weight (lbs) 29 3/4" x 43 13/16" x 24 15/32" Product (W x H x D) : Including Door 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D) : Including Hande 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D) : Opening Door 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D) : Opening Door 29 3/4" x 43 13/16" x 26 29/32" Cut-out (W x H x D) : Standard Min. 28 1/2" x 43 7/16" x 24 "Max. 28 5/8" x 43 1/2" x 24" Cut-out (W x H x D) : Flush 30" x 44" x 25" Overall Depth (in) - including hande TBD Overall Depth (in) - including hande TA Rating Catron Dimensions (Lower) (in) Rate Ant pload ADA		
DIMENSIONS/CLEARANCES/WEITS Product Weight (lbs) 204 Shipping Weight (lbs) 239 Product (W x H x D): Including Door 29 3/4" x 43 13/16" x 24 15/32" Product (W x H x D): Including Handle 29 3/4" x 43 13/16" x 45 2/32" Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 45 2/32" Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 45 2/1/32" Cut-out (W x H x D): Standard 28 5/8" x 43 1/2" x 24" Cut-out (W x H x D): Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Overall Depth (in) - including handle TBD Overall Depth (in) - including handle 24-1/2" (W) x 17-5/8" (H) x 17- 5/13" (D) Overall Depth (in) - including handle TBD Overall Depth (in) - including handle 70-8/11" (W) x 8-9/25" (H) x 17- 5/13" (D) Overall Depth (in) - including handle TBD Overall Depth (in) - including handle 70-8/11" (W) x 17-5/8" (H) x 18- 7/8" (D) Carton Dimensions (Lower) (in) 24-1/2" (W) x 17-5/8" (H) x 18- 7/8" (D) Carton Dimensions (in) (W x H x D) 30" x 50" x 30" POWER/RATINGS 60 Hz / 240 V, 208 V Requirements		•
Product Weight (lbs) 204 Shipping Weight (lbs) 239 Product (W x H x D): Including Door 29 3/4" x 43 13/16" x 24 15/32" Product (W x H x D): Including Handle 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 45 21/32" Cut-out (W x H x D): Standard 28 1/2" x 43 7/16" x 24"Max. 28 5/8" x 43 1/2" x 24" 28 5/8" x 43 1/2" x 24" Cut-out (W x H x D): Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Oven Interior Dimensions (Upper) (in) 20-8/11" (W) x 8-9/25" (H) x 17-5/13" (D) Oven Interior Dimensions (Lower) (in) 24-1/2" (W) x 17-5/8" (H) x 18-7/8" (D) Carton Dimensions (in) (W x H x D) 33" x 50" x 30" POWER/RATINGS 7/8" (D) Kating 7.8kW Required Power Supply 60 Hz / 240 V, 208 V ACCESSORIES 1EA Glast Tray(Upper) 1EA Rack(Upper) 1EA Griddle(Lower) 1EA Metal Tray(Upper) 1EA Heavy Duty Rack 2EA Gliding Rack 1EA	3	
Shipping Weight (lbs) 239 Product (W x H x D): Including Door 29 3/4" x 43 13/16" x 24 15/32" Product (W x H x D): Including Handle 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 26 29/32" Cut-out (W x H x D): Standard Xin 28 1/2" x 43 7/16" x 24"Max. Z8 5/8" x 43 1/2" x 24" Cut-out (W x H x D): Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Cut-out (W x H x D): Flush 30" x 44" x 25" Oven Interior Dimensions (Uoper) (in) 20-8/11"(W) x 8-9/25"(H) x 17-5/7(3"(D) 27-1/2"(W) x 17-5/8"(H) x 18-7/8"(D) Carton Dimensions (in) (W x H x D) 30" x 50" x 30" POWER/RATINGS Max. Amp load 40A Required Power Supply 60 Hz / 240 V, 208 V Accessores E Glass Tray(Upper) 1EA Rating 7.8kW Requirements 60 Hz / 240 V, 208 V Accessores E E E Griddle(Lower) 1EA E E		
Image Image Image Product (W x H x D): Including Door 29 3/4" x 43 13/16" x 24 15/32" Product (W x H x D): Including Handle 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 45 21/32" Cut-out (W x H x D): Standard Min. 28 1/2" x 43 7/16" x 24"Max. Cut-out (W x H x D): Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Overall Depth (in) - including handle TBD Over Interior Dimensions (Upper) (in) 20-8/11"(W) x 8-9/25"(H) x 17-5/8"(H) x 18-7/8"(D) Oven Interior Dimensions (Lower) (in) 24-1/2"(W) x 17-5/8"(H) x 18-7/8"(D) Oven Interior Dimensions (in) (W x H x D) 33" x 50" x 30" POWER/RATINGS 60 Hz / 240 V, 208 V Required Power Supply 60 Hz / 240 V, 208 V Accessores 60 Hz / 240 V, 208 V Accessores 1EA Rating 7.8kW Required Power Supply 1EA Rack(Upper) 1EA Rack(Upper) 1EA Rack(Upper) 1EA Metal Tray(Uper) 1EA Heavy Duty Rack	5 ()	
Product (W x H x D): Including Handle 29 3/4" x 43 13/16" x 26 29/32" Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 45 21/32" Cut-out (W x H x D): Standard Min. 28 1/2" x 43 7/16" x 24"Max. 28 5/8" x 43 1/2" x 24" Cut-out (W x H x D): Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Over Interior Dimensions (Upper) (in) 20-4/11" (W) x 8-9/25" (H) x 17- 5/13" (D) Oven Interior Dimensions (Lower) (in) 24-1/2" (W) x 17-5/8" (H) x 18- 7/8" (D) Oven Interior Dimensions (I) (W x H x D) 350" x 30" POWER/RATINGS 40A Required Power Supply 60 Hz / 240 V, 208 V Accessories 60 Hz / 240 V, 208 V Accessories 1EA Requirements 60 Hz / 240 V, 208 V Accessories 1EA Requirements 60 Hz / 240 V, 208 V Accessories 1EA Reduirements 1EA Reduirements 26 Hz / 240 V, 208 V Accessories 1EA Reduirements 1EA Reduirements 1EA Reak (Upper) 1EA Heavy Du		
Product (W x H x D): Opening Door 29 3/4" x 43 13/16" x 45 21/32" Cut-out (W x H x D): Standard Min. 28 1/2" x 43 7/16" x 24"Max. 28 5/8" x 43 1/2" x 24" Cut-out (W x H x D): Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Overall Depth (in) - including handle TA Max Amp load 40A Restring handle Reacy and plant 60 Hz / 240 V, 208 V Reatrong Rack(Upper)		
Cut-out (W x H x D) : Standard Min. 28 1/2" x 43 7/16" x 24"Max. 28 5/8" x 43 1/2" x 24" Cut-out (W x H x D) : Flush 30" x 44" x 25" Overall Depth (in) - including handle TBD Oven Interior Dimensions (Upper) (in) 20-8/11"(W) x 8-9/25"(H) x 17- 5/13"(D) Oven Interior Dimensions (Lower) (in) 24-1/2"(W) x 17-5/8"(H) x 18- 7/8"(D) Oven Interior Dimensions (Lower) (in) 24-1/2"(W) x 17-5/8"(H) x 18- 7/8"(D) Oven Interior Dimensions (Lower) (in) 24-1/2"(W) x 17-5/8"(H) x 18- 7/8"(D) Carton Dimensions (in) (W x H x D) 33" x 50" x 30" POWER/RATINGS 40A Required Power Supply 60 Hz / 240 V, 208 V Rating 7.8kW Requirements 60 Hz / 240 V, 208 V ACCESSORIES 500 Hz / 240 V, 208 V Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Broiler pan 1EA Broiler pan 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Heavy Duty Rack 2EA Gliding Rack 1EA HirtD WARRANTY Years Parts & Labo		
Cut-out (W × H × D): Standard 28 5/8" × 43 1/2" × 24" Cut-out (W × H × D): Flush 30" × 44" × 25" Overall Depth (in) - including handle TBD Overall Depth (in) - including handle TBD Over Interior Dimensions (Upper) (in) 20-8/11"(W) × 8-9/25"(H) × 17- 5/13"(D) Oven Interior Dimensions (Lower) (in) 24-1/2"(W) × 17-5/8"(H) × 18- 7/8"(D) Carton Dimensions (in) (W × H × D) 33" × 50" × 30" POWER/RATINGS 40A Required Power Supply 60 Hz / 240 V, 208 V Rating 7.8kW Requirements 60 Hz / 240 V, 208 V ACCESSORIES 1EA Glass Tray(Upper) 1EA Broiler pan 1EA Broiler pan 1EA Griddle(Lower) 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA Air Fry Rack(Lower) 2 Years VCES6428F (Smudge Resistant 195124024133		
Overall Depth (in) - including handle TBD Oven Interior Dimensions (Upper) (in) (W × H × D) 20-8/11"(W) × 8-9/25"(H) × 17- 5/13"(D) Oven Interior Dimensions (Lower) (in) 24-1/2"(W) × 17-5/8"(H) × 18- 7/8"(D) Oven Interior Dimensions (Lower) (in) 24-1/2"(W) × 17-5/8"(H) × 18- 7/8"(D) Carton Dimensions (in) (W × H × D) 33" × 50" × 30" POWER/RATINGS 33" × 50" × 30" POWER/RATINGS 60 Hz / 240 V, 208 V Required Power Supply 60 Hz / 240 V, 208 V Requirements 60 Hz / 240 V, 208 V ACCESSORIES 500 Hz / 240 V, 208 V Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Broiler pan 1EA Griddle(Lower) 1EA Metal probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY 7 Parts & Labour 2 Years UPC CODES 195124024133	Cut-out (W x H x D) : Standard	
Oven Interior Dimensions (Upper) (in) (W × H × D) 20-8/11"(W) × 8-9/25"(H) × 17- 5/13"(D) Oven Interior Dimensions (Lower) (in) (W × H × D) 24-1/2"(W) × 17-5/8"(H) × 18- 7/8"(D) Oven Interior Dimensions (in) (W × H × D) 33" × 50" × 30" POWER/RATINGS 33" × 50" × 30" POWER/RATINGS 60 Hz / 240 V, 208 V Required Power Supply 60 Hz / 240 V, 208 V Rating 7.8kW Requirements 60 Hz / 240 V, 208 V AcCESSORIES Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Broiler pan 1EA Griddle(Lower) 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Years Parts & Labour 2 Years UPC CODES Years	Cut-out (W x H x D) : Flush	30" x 44" x 25"
(W + H × D) 5/13"(D) Oven Interior Dimensions (Lower) (in) 24-1/2"(W) × 17-5/8"(H) × 18- 7/8"(D) Carton Dimensions (in) (W × H × D) 33" × 50" × 30" POWER/RATINGS 33" × 50" × 30" POWER/RATINGS 60 Hz / 240 V, 208 V Rating 7.8kW Required Power Supply 60 Hz / 240 V, 208 V Adx. Amp load 60 Hz / 240 V, 208 V Rating 7.8kW Requirements 60 Hz / 240 V, 208 V ACCESSORIES 500 Hz / 240 V, 208 V Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Stroide (Lower) 1EA Griddle(Lower) 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY 1 Parts & Labour 2 Years UPC CODES 1 WCES6428F (Smudge Resistant 195124024133	Overall Depth (in) - including handle	TBD
(W x H x D) 7/8"(D) Carton Dimensions (in) (W x H x D) 33" x 50" x 30" POWER/RATINGS 34" x 50" x 30" Max Amp load 40A Required Power Supply 60 Hz / 240 V, 208 V Rating 7.8kW Requirements 60 Hz / 240 V, 208 V ACCESSORIES 60 Hz / 240 V, 208 V Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Broiler pan 1EA Griddle(Lower) 1EA Metal probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour VCCS6428F (Smudge Resistant 195124024133		
POWER/RATINGSMax. Amp load40ARequired Power Supply60 Hz / 240 V, 208 VRating7.8kWRequirements60 Hz / 240 V, 208 VACCESSORIESGlass Tray(Upper)1EAMetal Tray(Upper)1EARack(Upper)1EAGriddle(Lower)1EAGiding Rack1EAGiding Rack1EALIMITED WARANTYParts & LabourParts & Labour2 YearsUPC CODES185/24024133		
Max. Amp load 40A Required Power Supply 60 Hz / 240 V, 208 V Rating 7.8kW Requirements 60 Hz / 240 V, 208 V ACCESSORIES 60 Hz / 240 V, 208 V Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Groider pan 1EA Griddle(Lower) 1EA Meat probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA UHITED WARRANTY Parts & Labour VCES6428F (Smudge Resistant 195124024133	Carton Dimensions (in) (W x H x D)	33" x 50" x 30"
Required Power Supply 60 Hz / 240 V, 208 V Rating 7.8kW Requirements 60 Hz / 240 V, 208 V ACCESSORIES 60 Hz / 240 V, 208 V Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Rack(Upper) 1EA Broiler pan 1EA Metal probe 1EA Metal probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA LIMITED WARRANTY Parts & Labour VCES6428F (Smudge Resistant 195124024133	POWER/RATINGS	
Rating 7.8kW Requirements 60 Hz / 240 V, 208 V ACCESSORIES Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Rack(Upper) 1EA Broiler pan 1EA Metal Tray(Upper) 1EA Broiler pan 1EA Metal probe 1EA Metal probe 1EA Iding Rack 2EA Gliding Rack 1EA LIMITED WARRANTY Parts & Labour VCES6428F (Smudge Resistant 195124024133	Max. Amp load	40A
Requirements 60 Hz / 240 V, 208 V ACCESSORIES IEA Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Rack(Upper) 1EA Broiler pan 1EA Griddle(Lower) 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA UINITED WARRANTY Parts & Labour VCES6428F (Smudge Resistant 195124024133	Required Power Supply	60 Hz / 240 V, 208 V
ACCESSORIES Glass Tray(Upper) 1EA Metal Tray(Upper) 1EA Rack(Upper) 1EA Broiler pan 1EA Griddle(Lower) 1EA Meat probe 1EA Meat probe 1EA Gliding Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour 2 Years UPC CODES WCES6428F (Smudge Resistant 195124024133	Rating	7.8kW
Glass Tay(Upper) 1EA Metal Tray(Upper) 1EA Rack(Upper) 1EA Broiler pan 1EA Griddle(Lower) 1EA Meat probe 1EA Meaty Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour VCCS6428F (Smudge Resistant 195124024133	Requirements	60 Hz / 240 V, 208 V
Metal Tray(Upper) 1EA Rack(Upper) 1EA Broiler pan 1EA Griddle(Lower) 1EA Meat probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour VCES6428F (Smudge Resistant 195174024133	ACCESSORIES	
Rack(Upper) 1EA Broiler pan 1EA Griddle(Lower) 1EA Meat probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour VPCCSOES VVCES6428F (Smudge Resistant	Glass Tray(Upper)	1EA
Broiler pan 1EA Griddle(Lower) 1EA Meat probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour 2 Years UPC CODES WCES6428F (Smudge Resistant 195124024133	Metal Tray(Upper)	1EA
Griddle(Lower) 1EA Meat probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY 2 Years Parts & Labour 2 Years UPC CODES VVCES6428F (Smudge Resistant	Rack(Upper)	1EA
Meat probe 1EA Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour 2 Years UPC CODES VVCES6428F (Smudge Resistant 195174024133	Broiler pan	1EA
Heavy Duty Rack 2EA Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour 2 Years UPC CODES WCES6428F (Smudge Resistant 195174024133	Griddle(Lower)	1EA
Gliding Rack 1EA Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour 2 Years UPC CODES WCES6428F (Smudge Resistant 195174024133	Meat probe	1EA
Air Fry Rack(Lower) 1EA LIMITED WARRANTY Parts & Labour 2 Years UPC CODES WCES6428F (Smudge Resistant 195174024133	Heavy Duty Rack	2EA
LIMITED WARRANTY Parts & Labour 2 Years UPC CODES WCES6428F (Smudge Resistant 195174024133	Gliding Rack	1EA
Parts & Labour 2 Years UPC CODES WCES6428F (Smudge Resistant 195174024133	Air Fry Rack(Lower)	1EA
UPC CODES WCES6428F (Smudge Resistant 195174024133	LIMITED WARRANTY	
WCES6428F (Smudge Resistant 195174024133	Parts & Labour	2 Years
	UPC CODES	
		195174024133

© 2022 LG Electronics Canada, Inc. All rights reserved. «LG Life's Good» is a registered trademark of LG Corp. All other product and brand names are trademarks or registered trademarks of their respective owners. Design, features and specifications are subject to change without notice. Non-metric weights and measurements are approximate. Some features may require Internet access. Content and services may vary by product and are subject to change without notice. 01/05/22

LG STUDIO