

500 Series, Induction Cooktop, 24", Black NIT5460UC



The 500 Series Induction Cooktop is Sleek in Design and Offers Quick and Even Cooking Results.

- PreciseSelect® direct cooking level selection.
- SpeedBoost® adds even more power to speed up the cooking process.
- **ReStart:** if something boils over, the cooktop automatically turns itself off and saves the last selected setting.
- **Induction:** faster than gas and electric cooktops. Precise cooking, easy cleaning and more efficient.
- The smooth ceramic glass surface makes cooking and cleaning especially easy.

Technical Data

Sealed Burners : No Burners with booster : All

Dimension of 2nd heating element (in) : 11" Power of 2nd heating element (W) : 2.6 kW







Optional accessories

HEZ390210 : System pan diameter 15 cm HEZ390220 : System pan diameter 19 cm HEZ390230 : System pan diameter 21cm



500 Series, Induction Cooktop, 24", Black NIT5460UC

The 500 Series Induction Cooktop is Sleek in Design and Offers Quick and Even Cooking Results.

Design

- 3 Induction Cooking Zones
- PreciseSelect® Direct Cooking Level Selection (17 Settings)

Efficiency

- SpeedBoost® Adds Even More Power to Speed Up the Cooking Process
- PotSense™ Automatically Adjusts Cooking Element to the Size of the Pan Bottom

Convenience


- Use the Kitchen Timer to Measure Cooking Time or as a Reminder

Safety

- ChildLock Prevents the Cooktop from Being Accidentially Switched on. Locks Temperature Settings if in Use.
- Digital 2-Stage Residual Heat Indicator for Each Cooking Zone
- Wipe Protection Quickly Pauses Settings to Clean as You Go
- ReStart Quickly Reinstates Previous Settings



500 Series, Induction Cooktop, 24", Black NIT5460UC



max. 2³/4" (68.5)

+ fitting/conduit 1" (23)

12" (300) approx.


min. 1" (26)
air clearance

"J" box

conduit approx.
36" (~900)

measurements in inches (mm)

* Minimum distance from the hob cut-out 30" Built-in oven – under induction cooktop



Dimensions based on standard countertop heigh (36" with 4³/₄" toe kick including base plate).

The built-in oven can be installed below the induction cooktop as long as there is a minimum 1* (26) clearance between the bottom of the cooktop and the top of the oven.

measurements in inches (mm)

